




Single Zone Ductless Heat Pump Systems




GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

Single Zone Solutions



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.




-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with up to 100% heating capacity at 5°F.



WARM START & AUTO START

Warm start ensures the fan does not blow cold air during heating mode startup. Auto restart automatically restarts the system after a power outage for seamless operation.



MOUNTING TEMPLATE/PLATE

A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.



EXTENDED KICKSTAND

The built-in bracket provides extra room for easier installation and service.



2-WAY PIPING DRAIN

Flexible right or left side condensation drain options simplify installation.



EASY-ACCESS PCB

The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.



TURBO MODE


Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



INDOOR AIR FILTER


The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.

ADDITIONAL PREMIUM HIGHWALL FEATURES



3-D AIRFLOW

Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.



SMART SENSOR

Automatically changes to an energy-saving temperature while you are away, then back to your regular setting when you return.



FOLLOW & SURROUND

Allows the user to choose if the air is directed towards them (follow) or away from them (surround).

Note: Features vary by individual models.




Highwall Specifications




PREMIUM HIGHWALL				STANDARD HIGHWALL	
					
					
1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA	1Q24RT2BEA	1Q3036RT2BEA	1Q3036RT2BEA
QS09WP2BEA	QS12WP2BEA	QS18WP2BEA	QS24WP2BEA	QS30WB2BEA	QS36WB2BEA
9,000	12,000	17,000	24,000	30,000	32,400
3,200-10,000	4,200-13,000	6,000-18,500	4,500-26,000	6,000-31,000	6,000-33,500
27	25	20.5	20	20	20
12.5	12.5	12	11.2	11.2	10.5
2.30	3.80	4.80	6	7.5	7.9
10,000	14,500	19,000	24,000	31,000	37,000
3,600-12,000	3,600-15,500	5,600-21,000	4,000-26,000	6,500-32,500	6,500-37,000
11.0	11.0	10.0	9.5	9.5	9.5
10,000	14,500	19,000	22,000	25,800	26,200
100%	100%	100%	92%	83%	71%
1.8	1.8	1.8	1.8	1.8	1.8
23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)
-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)
208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
20	20	30	30	40	40
13	14	20	22	25	25
15	15	20	25	30	30
DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
54	55	60	64	72	73
25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)	30 1/8 x 40 3/16 x 17 1/8 (765 x 1021 x 435)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)
83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)	134.7/173.06 (61.1/78.5)	165.42/211.64 (75/96)	165.42/211.64 (75/96)
Yes	Yes	Yes	Yes	Yes	Yes
5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
395/355/310/260/170	410/370/280/210/170	580/530/480/400/350	800/730/630/535/440	800/725/650/510/430	840/765/690/550/470
395/355/290/220/170	420/390/350/310/180	580/530/450/350/320	800/730/630/535/440	800/725/650/510/430	840/765/690/550/470
44/42/36/32/27	46/44/38/32/25	51/50/44/37/25	54/50/47/44/38	55/53/49/44/40	56/54/50/44/40
43/41/37/32/29	43/42/39/36/25	49/47/40/35/26	54/50/47/44/38	55/53/49/44/40	56/54/50/44/40
Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	No	No
5/8	5/8	5/8	5/8	5/8	5/8
12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 7/8 x 39 3/4 x 8 3/4 (327 x 1009 x 223)	13 1/2 x 44 1/2 x 9 1/8 (343 x 1129 x 232)	14 3/8 x 52 3/4 x 10 3/4 (365 x 1341 x 274)	14 3/8 x 52 3/4 x 10 3/4 (365 x 1341 x 274)
24.49/30.56 (11.1/13.85)	24.49/30.56 (11.1/13.85)	29.57/36.63 (13.4/16.6)	34.86/43.03 (15.8/19.5)	46.34/56.27 (21/25.5)	46.34/56.27 (21/25.5)
No	No	No	No	No	No
Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)
Built-In	Built-In	Built-In	Built-In	Built-In	Built-In
R454B	R454B	R454B	R454B	R454B	R454B
Flare	Flare	Flare	Flare	Flare	Flare
1/4	1/4	1/4	1/4	3/8	3/8
3/8	3/8	1/2	1/2	5/8	5/8
46.6	50.1	58.6	77.7	109.4	109.4
66/20	66/20	83/25	165/50	165/50	165/50
33/10	33/10	50/15	100/30	100/30	100/30

Single Zone Solutions



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.




-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with up to 100% heating capacity at 5°F.



WARM START & AUTO START

Warm start ensures the fan does not blow cold air during heating mode startup. Auto restart automatically restarts the system after a power outage for seamless operation.




MOUNTING TEMPLATE/PLATE

A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.



EXTENDED KICKSTAND

The built-in bracket provides extra room for easier installation and service.



2-WAY PIPING DRAIN

Flexible right or left side condensation drain options simplify installation.



EASY-ACCESS PCB

The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.



TURBO MODE


Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



INDOOR AIR FILTER

The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.

ADDITIONAL PREMIUM HIGHWALL FEATURES



3-D AIRFLOW

Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.



SMART SENSOR

Automatically changes to an energy-saving temperature while you are away, then back to your regular setting when you return.



FOLLOW & SURROUND

Allows the user to choose if the air is directed towards them (follow) or away from them (surround).

Note: Features vary by individual models.



Highwall Specifications


9K-24K Premium Highwall Includes Built-In Refrigerant Detection Sensor (RDS)




		PREMIUM HIGHWALL				STANDARD HIGHWALL	
							
		1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA	1Q24RT2BEA	1Q3036RT2BEA	1Q3036RT2BEA
		QS09WP2BEB	QS12WP2BEB	QS18WP2BEB	QS24WP2BEB	QS30WB2BEA	QS36WB2BEA
Cooling	Outdoor Unit						
	Indoor Unit						
	Rated Capacity Btu/hr	9,000	12,000	17,000	24,000	30,000	32,400
	Capacity Range Btu/hr	3,200-10,000	4,200-13,000	6,000-18,500	4,500-26,000	6,000-31,000	6,000-33,500
	SEER2	27	25	20.5	20	20	20
Heating	EER2	12.5	12.5	12	11.2	11.2	10.5
	Moisture Removal Pt./hr	2.30	3.80	4.80	6	7.5	7.9
	Rated Heating Capacity 47°F Btu/hr	10,000	14,500	19,000	24,000	31,000	37,000
	Heating Capacity Range Btu/hr	3,600-12,000	3,600-15,500	5,600-21,000	4,000-26,000	6,500-32,500	6,500-37,000
	HSPF2 (IV)	11.0	11.0	10.0	9.5	9.5	9.5
Operating Range	Rated Heating Capacity 5°F Btu/hr	10,000	14,500	19,000	22,000	25,800	26,200
	Heating Capacity at 5°F / Capacity at 47°F	100%	100%	100%	92%	83%	71%
	COP 5°F	1.8	1.8	1.8	1.8	1.8	1.8
	Cooling (Without Wind Baffle or Top Cover)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Over-Current Protection (MOP) A	20	20	30	30	40	40
	Minimum Circuit Amp A	13	14	20	22	25	25
	Recommended Breaker Size	15	15	20	25	30	30
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60	64	72	73
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)	30 1/8 x 40 3/16 x 17 1/8 (765 x 1021 x 435)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)	134.7/173.06 (61.1/78.5)	165.42/211.64 (75/96)	165.42/211.64 (75/96)
	Basepan Heater	Yes	Yes	Yes	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	395/355/310/260/170	410/370/280/210/170	580/530/480/400/350	800/730/630/535/440	800/725/650/510/430	840/765/690/550/470
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	395/355/290/220/170	420/390/350/310/180	580/530/450/350/320	800/730/630/535/440	800/725/650/510/430	840/765/690/550/470
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/42/36/32/27	46/44/38/32/25	51/50/44/37/25	54/50/47/44/38	55/53/49/44/40	56/54/50/44/40
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/41/37/32/29	43/42/39/36/25	49/47/40/35/26	54/50/47/44/38	55/53/49/44/40	56/54/50/44/40
	Auto Up-Down Louver	Yes	Yes	Yes	Yes	Yes	Yes
	Auto Left-Right Louver	Yes	Yes	Yes	Yes	No	No
	Drain Pipe Size O.D in	5/8	5/8	5/8	5/8	5/8	5/8
	Dimension: H x W x D in (mm)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 7/8 x 39 3/4 x 8 3/4 (327 x 1009 x 223)	13 1/2 x 44 1/2 x 9 1/8 (343 x 1129 x 232)	14 3/8 x 52 3/4 x 10 3/4 (365 x 1341 x 274)	14 3/8 x 52 3/4 x 10 3/4 (365 x 1341 x 274)
	Weight (Net/Ship) - lbs (kg)	24.49/30.56 (11.1/13.85)	24.49/30.56 (11.1/13.85)	29.57/36.63 (13.4/16.6)	34.86/43.03 (15.8/19.5)	46.34/56.27 (21/25.5)	46.34/56.27 (21/25.5)
	Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes	Yes	No	No
	Refrigerant Detection Sensor (RDS) Compatible	-	-	-	-	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)
Refrigerant Lines	WiFi*	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In
	Refrigerant	R454B	R454B	R454B	R454B	R454B	R454B
	Connections	Flare	Flare	Flare	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4	1/4	3/8	3/8
	Suction O.D. in	3/8	3/8	1/2	1/2	5/8	5/8
	Factory Charge Oz	46.6	50.1	58.6	77.7	109.4	109.4
	Maximum Line Length Ft / m	66/20	66/20	83/25	165/50	165/50	165/50
	Maximum Height Ft / m	33/10	33/10	50/15	100/30	100/30	100/30

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

Single Zone Solutions



OPERATING RANGE (°F):



CONVENIENT MODERN DESIGN

Flexible installation accommodates ceilings of various heights, and the sleek, recessed design fits between 16" ceiling joists for easy installation.



ROOM TEMPERATURE DISPLAY

Easy-to-read dual seven segment display on the front of the panel.



EASY-ACCESS PCB

The PCB and motor can be easily removed for quick component and wiring checks.



WARM START

Ensures the fan does not blow cold air during heating mode startup.



CONDENSATE PUMP

Factory-installed condensate pump with up to 47 1/4" lift height.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.




FRESH AIR KNOCKOUT

Unit designed with a 3" round fresh air knockout.



INDOOR AIR FILTER

The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.



3-D AIRFLOW

Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.

Note: Features vary by individual models.



One-Way Compact Cassette Specifications




	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA
	Indoor Unit	US09AB2BEA	US12AB2BEA	US18AB2BEA
	Panel (required, sold separately)	QAABP0718A	QAABP0718A	QAABP0718A
Cooling	Rated Capacity Btu/hr	9,000	12,000	17,000
	Capacity Range Btu/hr	2,400-9,000	2,900-12,000	4,900-17,000
	SEER2	25	24.5	21
	EER2	14.6	14	12
	Moisture Removal Pt./hr	2	2.6	4
Heating	Rated Heating Capacity 47°F Btu/hr	11,000	12,600	19,000
	Heating Capacity Range Btu/hr	3,800-11,000	3,300-12,600	4,200-19,000
	HSPF2 (IV)	12	10	10.2
	Rated Heating Capacity 5°F Btu/hr	11,000	12,600	18,000
	Heating Capacity at 5°F / Capacity at 47°F	100%	100%	95%
	COP 5°F	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Over-Current Protection (MOP) A	20	20	30
	Minimum Circuit Amp A	13	14	20
	Recommended Breaker Size	15	15	20
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	55	55	60
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)
	Basepan Heater	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	365/325/285/245/205	375/335/295/255/215	415/370/330/290/250
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	385/345/310/280/240	415/400/360/320/280	440/420/390/355/315
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	40/39/36/32/28	40/39/36/33/29	45/43/40/37/34
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/39/37/35/30	42/39/37/36/32	46/44/43/40/37
	Auto Up-Down Louver	Yes	Yes	Yes
	Auto Left-Right Louver	Yes	Yes	Yes
	Dimension: H x W x D in (mm)	7 1/4 x 50 1/4 x 13 1/4 (185 x 1277 x 335)	7 1/4 x 50 1/4 x 13 1/4 (185 x 1277 x 335)	7 1/4 x 50 1/4 x 13 1/4 (185 x 1277 x 335)
	Weight (Net/Ship) - lbs (kg)	41.4/76.7 (18.8/34.8)	42.1/78.9 (19.1/35.8)	42.1/78.9 (19.1/35.8)
	Drain Pipe Size O.D. in	1*	1*	1*
	Condensate Pump	Yes	Yes	Yes
	Max. Drain-Lift Height in (mm)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)
	Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No
	Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)
Refrigerant Lines	WiFi**	Built-In	Built-In	Built-In
	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	46.6	50.1	58.6
	Maximum Line Length Ft / m	66/20	66/20	83/25
	Maximum Height Ft / m	33/10	33/10	50/15


*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

Single Zone Solutions



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.




-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with up to 100% heating capacity at 5°F.



AUTO RESTART

Automatically restarts the system after a power outage for seamless operation without manual intervention.



COMPACT DESIGN

Fits 2' x 2' drop ceiling for easy installation.



CONDENSATE PUMP

Factory-installed condensate pump.



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



FRESH AIR KNOCKOUT

Unit designed with a 4" round fresh air knockout.



INDEPENDENT LOUVER CONTROL

The four cassette louvers can be set to the same, or different positions, to control airflow direction.

Note: Features vary by individual models.



4-Way Compact Cassette Specifications



	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA
	Indoor Unit	US09CB2BEA	US12CB2BEA	US18CB2BEA
	Panel (required, sold separately)	QACCP01WA	QACCP01WA	QACCP01WA
Cooling	Rated Capacity Btu/hr	9,000	12,000	18,000
	Capacity Range Btu/hr	3,000-10,000	3,000-13,000	6,000-19,000
	SEER2	20	20	20
	EER2	12	12	12
	Moisture Removal Pt./hr	2.40	3.50	5.50
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	12,500	18,000
	Heating Capacity Range Btu/hr	3,000-11,000	3,000-14,000	6,000-19,500
	HSPF2 (IV)	10.0	10.0	10.0
	Rated Heating Capacity 5°F Btu/hr	9,000	10,000	14,400
	Heating Capacity at 5°F / Capacity at 47°F	90%	80%	80%
	COP 5°F	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Over-Current Protection (MOP) A	20	20	30
	Minimum Circuit Amp A	13	14	20
	Recommended Breaker Size	15	15	20
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)
	Basepan Heater	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	458/425/387/345/302
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	479/441/387/345/302
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32
	Auto Up-Down Louver	Yes	Yes	Yes
	Auto Left-Right Louver	No	No	No
	Dimension: H x W x D in (mm)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)
	Weight (Net/Ship) - lbs (kg)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)
	Drain Pipe Size O.D in	1*	1*	1*
	Condensate Pump	Built-In	Built-In	Built-In
	Max. Drain-Lift Height in (mm)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)
	Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No
	Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)
	WiFi**	Built-In	Built-In	Built-In
Refrigerant Lines	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	46.6	50.1	58.6
	Maximum Line Length Ft / m	66/20	66/20	83/25
	Maximum Height Ft / m	33/10	33/10	50/15


*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

Single Zone Solutions



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.



-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with up to 100% heating capacity at 5°F.



AUTO RESTART

Automatically restarts the system after a power outage for seamless operation without manual intervention.



CONDENSATE PUMP

Factory-installed condensate pump.



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



FRESH AIR KNOCKOUT

Unit designed with a 4" round fresh air knockout.



INDEPENDENT LOUVER CONTROL

The four cassette louvers can be set to the same, or different positions, to control airflow direction.

Note: Features vary by individual models.



4-Way Large Cassette Specifications



	Outdoor Unit	1Q24RT2BEA	1Q3036RT2BEA	1Q3036RT2BAA
	Indoor Unit	US24LB2BEA	US30LB2BEA	US36LB2BEA
	Panel (required, sold separately)	QALCP01WA	QALCP01WA	QALCP01WA
Cooling	Rated Capacity Btu/hr	24,000	30,000	36,000
	Capacity Range Btu/hr	6,000-25,000	9,000-32,000	9,000-37,500
	SEER2	20	20	19
	EER2	12	12	11
	Moisture Removal Pt./hr	3.78	5.00	6.63
Heating	Rated Heating Capacity 47°F Btu/hr	26,000	32,000	37,000
	Heating Capacity Range Btu/hr	6,000-27,000	9,000-33,500	9,000-38,500
	HSPF2 (IV)	10.0	10.0	10.0
	Rated Heating Capacity 5°F Btu/hr	22,000	27,000	29,000
	Heating Capacity at 5°F / Capacity at 47°F	85%	84%	78%
	COP 5°F	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)
	Heating	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Over-Current Protection (MOP) A	30	40	40
	Minimum Circuit Amp A	22	25	25
	Recommended Breaker Size	25	30	30
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	68	72	73
	Dimension: H x W x D in (mm)	30 1/8 x 40 3/16 x 17 1/8 (765 x 1021 x 435)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)
	Weight (Net/Ship) - lbs (kg)	134.7/173.06 (61.1/78.5)	165.42/211.64 (75/96)	165.42/211.64 (75/96)
	Basepan Heater	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	1033/873/858/640/400	1247/1200/1033/873/650	1247/1200/1033/873/650
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	1033/873/858/640/400	1247/1200/1033/873/650	1247/1200/1033/873/650
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	46/44/41/38/35	51/50/45/44/39	51/50/45/44/39
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	46/44/42/39/36	51/50/45/44/39	51/50/45/44/39
	Auto Up-Down Louver	Yes	Yes	Yes
	Auto Left-Right Louver	No	No	No
	Dimension: H x W x D in (mm)	9 3/4 x 33 x 33 (248 x 840 x 840)	9 3/4 x 33 x 33 (248 x 840 x 840)	9 3/4 x 33 x 33 (248 x 840 x 840)
	Weight (Net/Ship) - lbs (kg)	56.22/85.32 (25.5/38.7)	56.22/85.32 (25.5/38.7)	56.22/85.32 (25.5/38.7)
	Drain Pipe Size O.D in	1"	1"	1"
	Condensate Pump	Built-In	Built-In	Built-In
	Max. Drain-Lift Height in (mm)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)
	Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No
	Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)
	WiFi**	Built-In	Built-In	Built-In
Refrigerant Lines	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	3/8	3/8	3/8
	Suction O.D. in	5/8	3/4	3/4
	Factory Charge Oz	77.7	109.4	109.4
	Maximum Line Length Ft / m	165/50	165/50	165/50
	Maximum Height Ft / m	100/30	100/30	100/30


*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

Single Zone Solutions



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.



-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with up to 100% heating capacity at 5°F.



AUTO RESTART

Automatically restarts the system after a power outage for seamless operation without manual intervention.



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



AIRFLOW DIRECTION CONTROL

Allows the homeowner to select preferred airflow direction - the top and bottom or top only.



INSTALLATION FLEXIBILITY

Unit can be placed on the floor or installed low on the wall.



ROOM TEMPERATURE DISPLAY

Easy-to-read dual seven segment display on the front of the panel.

Note: Features vary by individual models.



Console Specifications

with Built-In Refrigerant Detection Sensor (RDS)




	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA
	Indoor Unit	US09FB2BEA	US12FB2BEA	US18FB2BEA
Cooling	Rated Capacity Btu/hr	9,000	12,000	17,000
	Capacity Range Btu/hr	3,000-10,000	3,000-13,500	6,000-18,500
	SEER2	20	20	19
	EER2	12	12	9
	Moisture Removal Pt./hr	2.16	3.40	3.80
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	12,300	18,000
	Heating Capacity Range Btu/hr	2,500-10,000	2,500-13,000	6,000-19,000
	HSPF2 (IV)	10.5	9.5	9.5
	Rated Heating Capacity 5°F Btu/hr	9,000	10,000	14,400
	Heating Capacity at 5°F / Capacity at 47°F	90%	81%	80%
	COP 5°F	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Over-Current Protection (MOP) A	20	20	30
	Minimum Circuit Amp A	13	14	20
	Recommended Breaker Size	15	15	20
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)
	Basepan Heater	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	290/218/205/176/147	314/226/210/195/175	345/341/271/218/210
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	312/206/205/176/147	311/223/200/195/175	328/296/263/206/200
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/40/37/32/24	47/41/37/33/25	49/44/43/40/37
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/37/32/27/20	47/40/37/33/25	49/43/43/37/37
	Auto Up-Down Louver	Yes	Yes	Yes
	Auto Left-Right Louver	No	No	No
	Drain Pipe Size O.D in	5/8	5/8	5/8
	Dimension: H x W x D in (mm)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)
	Weight (Net/Ship) - lbs (kg)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)
	Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes
	WiFi*	Built-In	Built-In	Built-In
Refrigerant Lines	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	46.6	50.1	58.6
	Maximum Line Length Ft / m	66/20	66/20	83/25
	Maximum Height Ft / m	33/10	33/10	50/15

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

Single Zone Solutions



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.



-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with up to 100% heating capacity at 5°F.



AUTO RESTART

Automatically restarts the system after a power outage for seamless operation without manual intervention.




WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



COMPACT DESIGN

Less than 10" height saves ceiling space.



CONDENSATE PUMP

Factory-installed condensate pump.



0.6" EXTERNAL STATIC

Designed for static pressure up to 0.6" w.g.



FRESH AIR KNOCKOUT

Unit designed with a 4" round fresh air knockout.



AUXILIARY HEATER COMPATIBLE

Compatible with many third-party auxiliary heaters.



OPTIONAL ACCESSORIES

MERV filter box and supply plenums available (sold separately) for easy installation.

Note: Features vary by individual models.



Mid-Static Ducted Specifications

with Built-In Refrigerant Detection Sensor (RDS)



	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA	1Q24RT2BEA	1Q3036RT2BEA	1Q3036RT2BEA
	Indoor Unit	US09MB2BEA	US12MB2BEA	US18MB2BEA	US24MB2BEA	US30MB2BEA	US36MB2BEA
Cooling	Rated Capacity Btu/hr	9,000	10,000	18,000	24,000	30,000	36,000
	Capacity Range Btu/hr	3,000-10,000	3,000-11,000	6,000-19,000	6,000-25,000	9,000-31,000	9,000-36,500
	SEER2	19.6	19.8	18	18.2	17.6	17.4
	EER2	12	11.7	11.7	11.7	10.8	9.8
	Moisture Removal Pt./hr	1.10	1.18	3.80	4.19	5.07	7.6
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	14,000	20,000	26,000	32,000	36,000
	Heating Capacity Range Btu/hr	3,000-12,500	3,000-14,500	6,000-20,500	6,000-26,500	9,000-33,000	9,000-36,500
	HSPF2 (IV)	10.5	10.5	10.5	10.5	10	9.5
	Rated Heating Capacity 5°F Btu/hr	8,000	10,000	17,000	23,000	24,000	26,000
	Heating Capacity at 5°F / Capacity at 47°F	80%	71%	85%	88%	75%	72%
	COP 5°F	1.8	1.8	1.8	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)	23~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Over-Current Protection (MOP) A	20	20	30	30	40	40
	Minimum Circuit Amp A	13	14	20	22	25	25
	Recommended Breaker Size	15	15	20	25	30	30
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60	68	72	73
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)	30 1/8 x 40 3/16 x 17 1/8 (765 x 1021 x 435)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)	33 1/16 x 43 1/8 x 19 7/8 (840 x 1095 x 505)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)	134.7/173.06 (61.1/78.5)	165.42/211.64 (75/96)	165.42/211.64 (75/96)
	Basepan Heater	Yes	Yes	Yes	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	353/286/200/150/141	409/350/308/158/148	620/517/332/214/203	927/844/667/564/482	1236/1130/953/812/688	1236/1130/953/812/688
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	358/292/208/155/145	412/355/311/163/152	627/523/337/217/205	927/844/667/564/482	1236/1130/953/812/688	1236/1130/953/812/688
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36	44/43/42/40/38	46/45/41/38/36	46/45/41/38/36
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36	44/43/42/40/38	46/45/41/38/36	46/45/41/38/36
	Dimension: H x W x D in (mm)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 47 1/2 x 27 1/2 (248 x 1207 x 700)	9 3/4 x 47 1/2 x 27 1/2 (248 x 1207 x 700)	9 3/4 x 63 1/4 x 27 1/2 (248 x 1607 x 700)	9 3/4 x 63 1/4 x 27 1/2 (248 x 1607 x 700)
	Weight (Net/Ship) - lbs (kg)	62.17/86.86 (28.2/39.4)	62.17/86.86 (28.2/39.4)	87.74/123.46 (39.8/56)	87.74/123.46 (39.8/56)	115.08/158.29 (52.2/71.8)	115.08/158.29 (52.2/71.8)
	Drain Pipe Size O.D in	1"	1"	1"	1"	1"	1"
	Max. External Static Pressure in.W.G (Pa)	0.6 (150)	0.6 (150)	0.6 (150)	0.6 (150)	0.6 (150)	0.6 (150)
	Condensate Pump	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In
	Max. Drain-lift height in (mm)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)
	Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes	Yes	Yes	Yes
	WiFi**	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In
Refrigerant Lines	Refrigerant	R454B	R454B	R454B	R454B	R454B	R454B
	Connections	Flare	Flare	Flare	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4	3/8	3/8	3/8
	Suction O.D. in	3/8	3/8	1/2	5/8	3/4	3/4
	Factory Charge Oz	46.6	50.1	58.6	77.7	109.4	109.4
	Maximum Line Length Ft / m	66/20	66/20	83/25	165/50	165/50	165/50
	Maximum Height Ft / m	33/10	33/10	50/15	100/30	100/30	100/30

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.



Haier



LIMITED WARRANTY

We take pride in our workmanship; our standard coverage includes a 5-year limited warranty on parts.

Additionally, our ductless systems qualify for a 10-year limited warranty on parts with registration. To receive the extended coverage, equipment must be registered within 60 days of installation. Please refer to the warranty documentation for complete details.



To register your equipment go to:
www.geappliancesairandwater.com/warranty



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

