

2260DC • 60 cm Drinks Cabinets • 2000 Series

FEATURES & BENEFITS



PERFORMANCE

- Volume of 139 litres holds up to 79 bottles (330 ml) or 123 cans (330 ml) and 10 wine bottles (0,75 L)
- Digital Touch Pad Control is conveniently located on upper face of unit
- Temperature range: 1°C - 7°C
- Convection cooling system rapidly and efficiently takes items to the set temperature

INTERIOR/EXTERIOR

- Black interior is illuminated with LED lighting that automatically turns off when the door is closed, or can be set to stay on for 3 hours
- Full extension black coated wine racks allow for easy access and prevent bottles from shifting
- Wine racks accommodate a variety of bottle shapes and sizes
- Three adjustable tempered glass shelves with 7 height positions
- LowE coated, argon gas filled triple thermopane glass door provides protection from harmful UV light
- The door swing is field reversible and is shipped right-hand hinged

INTEGRATION

- Robust, concealed and covered hinges with built-in door stop and closer
- Integrated model requires 20 mm custom door panel of your choice, or can accept U-Line Euro Style Handleless Panel Accessory (must be ordered separately)
- Fixed grille can accept an integrated plinth
- Four independently adjustable leveling legs provide a precise undercounter fit



INTEGRATED FRAME



INTEGRATED SOLID



INTEGRATED FRAME
(STAINLESS
HANDLELESS PANEL)*



INTEGRATED SOLID
(STAINLESS
HANDLELESS PANEL)*

MODEL DETAILS

Model	Voltage	Door Swing	Finish	Shipping Weight
U-2260DCINT-00B	220-240 / 50	Field Reversible	Integrated Frame	67 kg
U-2260DCINT-60B	220-240 / 50	Field Reversible	Integrated Solid	64 kg

ACCESSORIES



Model	Description	Finish	Shipping Weight
ULASHP24FRAME*	Stainless Handleless Panel, 60 cm Frame	Stainless Frame	4 kg
ULASHP24SOLID*	Stainless Handleless Panel, 60 cm Solid	Stainless Solid	5 kg
U-POWERCORD-2056	Power Cord, 220-240v Great Britain/Ireland	Black	1 lb (0,5 kg)
U-POWERCORD-2667	Power Cord, 220-240v Continental Europe	Black	1 lb (0,5 kg)
U-POWERCORD-2256	Power Cord, 220-240v Australia/New Zealand	Black	1 lb (0,5 kg)
U-POWERCORD-3071	Power Cord, 220-240v China	Black	1 lb (0,5 kg)
U-POWERCORD-3111	Power Cord, 220-240v India	Black	1 lb (0,5 kg)

Power cord type must be specified with each U-Line order; no additional cost for power cord.

*Installs on integrated models.

2000 Series • 60 cm Drinks Cabinets • **2260DC**
NICHE / RECESS

Dimensions shown apply to Integrated (INT) models with a 20 mm integrated panel/frame installed (applies to U-Line's Euro Style Handleless Panel Accessory).


INSTALLATION NOTES

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

*Must be installed in a climate controlled environment and operate within the temperatures designated in this product's User Guide.

Please visit u-line.com to view this model's User Guide. All specifications are subject to change without notice.

PRODUCT FICHE

Model	2260DC
Category	3
Energy efficiency class on a scale of A+++ to G	A+
Energy consumption in kWh per year	117 kWh
Total volume: fridge compartment (net)	139 L
Total volume: wine compartment (net)	N/A
Total volume: freezer compartment (net)	N/A
Frost-free compartment	Yes
Temperature rise time in event of blackout (hrs)	N/A
Climate class	T or ST
Noise emissions	46 dBA
Dimensions: width	600 mm
Dimensions: depth	590 mm
Dimensions: height	856 mm
Net weight: solid door	59 kg
Net weight: glass door	62 kg
Panel type	70 mm Frame Panel or Solid Panel (-60 suffix)
Panel thickness	20 mm
Panel height	762 mm
Panel width	595 mm
Rated frequency	50 Hz
Rated voltage	220-240 v
Refrigerant charge	38 g
Foam blowing agent	HFO-1233zd

COOLING SYSTEM
