

MULTI-ZONE SOLUTIONS


Single zone features, benefits, and performance, available for multi-zone applications.

Matching one outdoor unit with a variety of multiple indoor units provides contractors unprecedented application flexibility.



Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet **ENERGY STAR® Criteria**.

Ask your contractor for details or visit www.energystar.gov.




GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

MULTI-ZONE SOLUTIONS



OPERATING RANGE (°F):



EASIER TO: DO THE JOB



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.

EASIER TO: CLOSE THE SALE



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



AUTO START

Auto restart automatically restarts the system after a power outage for seamless operation.

MULTI-ZONE OUTDOOR UNIT SPECIFICATIONS



2 Zones



3 Zones



4 Zones

		2G18AD2BEA	3G24AD2BEA	4G36AD2BEA
Cooling Non-Ducted	Rated Capacity Btu/hr	18,000	24,000	35,000
	Capacity Range Btu/hr	4,000-19,000	4,000-25,000	6,500-36,000
	SEER2	22.5	24.0	20.0
	EER2	12.0	12.0	10.0
Cooling Ducted	Rated Capacity Btu/hr	17,000	24,000	33,400
	Capacity Range Btu/hr	4,000-18,000	4,000-25,000	6,500-34,000
	SEER2	18.8	17.2	16.5
	EER2	10.8	10.5	8.8
Heating Non-Ducted	Rated Heating Capacity 47°F Btu/hr	21,000	27,000	36,000
	Capacity Range Btu/hr	4,000-22,000	4,000-28,000	6,500-37,000
	HSPF2 (IV)	10.5	10.2	10.0
	Rated Heating Capacity 5°F Btu/hr	16,600	17,600	23,000
	Heating Capacity at 5°F / Capacity at 47°F	79.0%	65.2%	63.9%
	COP @ 5°F / COP @ 47°F	1.8 / 3.6	1.8 / 3.9	1.8 / 3.2
Heating Ducted	Rated Heating Capacity 47°F Btu/hr	19,000	25,000	35,600
	Capacity Range Btu/hr	4,000-20,000	4,000-26,000	6,500-36,000
	HSPF2 (IV)	9.5	9.5	9.3
	Rated Heating Capacity 5°F Btu/hr	15,000	17,000	21,000
	Heating Capacity at 5°F / Capacity at 47°F	77.0%	67.0%	60.0%
	COP @ 5°F / COP @ 47°F	1.8 / 3.7	1.8 / 3.6	1.8 / 3.3
Operating Range	Cooling °F (°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)
	Heating °F (°C)	-4~75°F (-20~24°C)	-4~75°F (-20~24°C)	-4~75°F (-20~24°C)
Power Supply	Voltage, Cycle, Phase V/Hz/-	208-230/60/1	208-230/60/1	208-230/60/1
	Wire Size Between IDU and ODU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU
	Maximum Over-Current Protection (MOP) A	25	25	30
	Minimum Circuit Amp A	16	18	22
	Recommended Breaker Size	20	30	30
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Fan Speed RPM	200~700	200~700	250~780
	Outdoor Noise Level dB	52	53	58
	Dimension: Height in (mm)	27 9/16 (700)	27 9/16 (700)	30 1/8 (765)
	Dimension: Width in (mm)	36 (915)	36 (915)	37 3/16 (945)
	Dimension: Depth in (mm)	14 1/2 (368)	14 1/2 (368)	15 13/16 (402)
	Weight (Net/Ship)- lbs (kg)	112/130 (51/59)	119/137 (54/62)	134/152 (61/69)
	Basepan Heater	No	No	No
Refrigerant Lines	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4 1/4	1/4 1/4 1/4	1/4 1/4 1/4 1/4
	Suction O.D. in	3/8 3/8	3/8 3/8 3/8	3/8 3/8 3/8 1/2
	Factory Charge Oz	53	60	81
	Maximum Line Length Ft / m	98/30	197/60	230/70
	Maximum Height Ft / m	50/15	50/15	50/15
	Minimum Line Length for Each Individual Indoor Unit Ft / m	10/3	10/3	10/3
	Maximum Line Length for Each Individual Indoor Unit Ft / m	65/20	82/25	82/25
	Maximum Line Length without Additional Charge Ft / m	66/20	100/30	131/40

MULTI-ZONE SOLUTIONS



OPERATING RANGE (°F):



EASIER TO: DO THE JOB



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



AUTO START

Auto restart automatically restarts the system after a power outage for seamless operation.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.




-22°F HEATING

Reliable low ambient heating down to -22°F ensures comfort and efficiency even in extreme conditions.

MULTI-ZONE OUTDOOR UNIT SPECIFICATIONS



2 Zones



3 Zones

4 Zones

5 Zones



		2G20ED2BEA	3G24ED2BEA	4G36ED2BEA	5G42ED2BEA
Cooling Non-Ducted	Rated Capacity Btu/hr	18,000	24,000	36,000	42,000
	Capacity Range Btu/hr	4,000-19,000	4,000-25,000	6,500-36,500	6,500-42,500
	SEER2	20.6	23.0	20.5	20.5
	EER2	12.3	12.2	11.0	10.5
Cooling Ducted	Rated Capacity Btu/hr	17,000	24,000	35,000	42,000
	Capacity Range Btu/hr	4,000-18,000	4,000-25,000	6,500-35,500	6,500-42,500
	SEER2	17.6	17.2	17.4	17.4
	EER2	10.8	10.5	10.2	10.2
Heating Non-Ducted	Rated Heating Capacity 47°F Btu/hr	22,000	25,000	36,000	42,500
	Capacity Range Btu/hr	4,000-23,000	4,000-26,000	6,500-37,000	6,500-43,500
	HSPF2 (IV)	10.5	10.5	10.0	9.5
	Rated Heating Capacity 5°F Btu/hr	20,000	22,800	34,000	35,000
	Heating Capacity at 5°F / Capacity at 47°F	91%	91%	94%	81%
	COP @ 5°F / COP @ 47°F	1.8 / 3.7	1.8 / 3.6	1.8 / 3.7	1.8 / 3.6
Heating Ducted	Rated Heating Capacity 47°F Btu/hr	22,000	26,000	35,000	42,500
	Capacity Range Btu/hr	4,000-23,000	4,000-27,000	6,500-36,000	6,500-43,500
	HSPF2 (IV)	10.5	10.0	10.0	9.5
	Rated Heating Capacity 5°F Btu/hr	20,000	22,000	30,000	35,000
	Heating Capacity at 5°F / Capacity at 47°F	90%	85%	84%	83%
	COP @ 5°F / COP @ 47°F	1.8 / 3.6	1.8 / 3.5	1.8 / 3.9	1.8 / 3.5
Operating Range	Cooling °F (°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)	14~115°F (-10~46°C)
	Heating °F (°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)	-22~75°F (-30~24°C)
Power Supply	Voltage, Cycle, Phase V/Hz/-	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
	Wire Size Between IDU and ODU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU	14/4 AWG Stranded for L1, L2, C, G between ODU and each IDU; and 16/2 AWG Stranded Shielded for H1, H2 between ODU and nearest IDU
	Maximum Over-Current Protection (MOP) A	30	30	40	40
	Minimum Circuit Amp A	20	21	35	36
	Recommended Breaker Size	20	30	40	40
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Fan Speed RPM	250~780	250~780	250~650	250~650
	Outdoor Noise Level dB	57	57	60	62
	Dimension: Height in (mm)	30 1/8 (765)	30 1/8 (765)	33 1/16 (840)	33 1/16 (840)
	Dimension: Width in (mm)	37 3/16 (945)	37 3/16 (945)	41 3/4 (1060)	41 3/4 (1060)
	Dimension: Depth in (mm)	15 13/16 (402)	15 13/16 (402)	15 13/16 (402)	15 13/16 (402)
	Weight (Net/Ship) - lbs (kg)	130/148 (59/67)	132/150 (60/68)	198/243 (90/110)	201/245 (91/111)
	Basepan Heater	Yes	Yes	Yes	Yes
Refrigerant Lines	Refrigerant	R454B	R454B	R454B	R454B
	Connections	Flare	Flare	Flare	Flare
	Liquid O.D. in	1/4 1/4	1/4 1/4 1/4	1/4 1/4 1/4 1/4	1/4 1/4 1/4 1/4 1/4
	Suction O.D. in	3/8 3/8	3/8 3/8 3/8	3/8 3/8 3/8 1/2	3/8 3/8 3/8 1/2 1/2
	Factory Charge Oz	60	71	113	123
	Maximum Line Length Ft / m	164/50	197/60	230/70	262/80
	Maximum Height Ft / m	50/15	50/15	50/15	50/15
	Minimum Line Length for Each Individual Indoor Unit Ft / m	10/3	10/3	10/3	10/3
	Maximum Line Length for Each Individual Indoor Unit Ft / m	82/25	82/25	82/25	82/25
	Maximum Line Length Without Additional Charge Ft / m	66/20	100/30	131/40	164/50

MULTI-ZONE

OUTDOOR/INDOOR MATCHING TABLE



POWERED BY
SmartHQ™

OUTDOOR UNITS



		2G18AD2BEA	3G24AD2BEA	4G36AD2BEA	2G20ED2BEA	3G24ED2BEA	4G36ED2BEA	5G42ED2BEA
	Standard Highwall	GS07WB2BEA	✓	✓	✓	✓	✓	✓
		GS09WB2BEA	✓	✓	✓	✓	✓	✓
		GS12WB2BEA	✓	✓	✓	✓	✓	✓
		GS15WB2BEA	✓	✓	✓	✓	✓	✓
		GS18WB2BEA		✓		✓	✓	✓
		GS24WB2BEA		✓			✓	✓
	Premium Highwall	GS06WP2BEA	✓	✓	✓	✓	✓	✓
		GS09WP2BEA	✓	✓	✓	✓	✓	✓
		GS09WP2BEB	✓	✓	✓	✓	✓	✓
		GS12WP2BEA	✓	✓	✓	✓	✓	✓
		GS12WP2BEB	✓	✓	✓	✓	✓	✓
		GS18WP2BEA		✓		✓	✓	✓
		GS18WP2BEB		✓		✓	✓	✓
		GS24WP2BEA		✓			✓	✓
	One-Way Cassette	US07AB2BEA	✓	✓	✓	✓	✓	✓
		US09AB2BEA	✓	✓	✓	✓	✓	✓
		US12AB2BEA	✓	✓	✓	✓	✓	✓
		US18AB2BEA		✓		✓	✓	✓
	4-Way Compact Cassette	US09CB2BEA	✓	✓	✓	✓	✓	✓
		US12CB2BEA	✓	✓	✓	✓	✓	✓
		US18CB2BEA		✓		✓	✓	✓
	4-Way Large Cassette	US24LB2BEA		✓			✓	✓
	Floor Console	US09FB2BEA	✓	✓	✓	✓	✓	✓
		US12FB2BEA	✓	✓	✓	✓	✓	✓
		US18FB2BEA		✓		✓	✓	✓
	Mid-Static Ducted	US09MB2BEA	✓	✓	✓	✓	✓	✓
		US12MB2BEA	✓	✓	✓	✓	✓	✓
		US18MB2BEA		✓		✓	✓	✓
		US24MB2BEA		✓			✓	✓

MULTI-ZONE INDOOR UNIT SPECIFICATIONS

STANDARD HIGHWALL




EASIER TO: DO THE JOB



EXTENDED KICKSTAND

The built-in bracket provides extra room for easier installation and service.



MOUNTING TEMPLATE/PLATE

A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.



2-WAY PIPING DRAIN

Flexible right or left side condensation drain options simplify installation.



EASY-ACCESS PCB

The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.

EASIER TO: CLOSE THE SALE



AUTO LOUVER

Designed to oscillate up and down automatically for even air distribution.



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



INDOOR AIR FILTER

The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.

	GS07WB2BEA	GS09WB2BEA	GS12WB2BEA	GS15WB2BEA	GS18WB2BEA	GS24WB2BEA
Rated Capacity Btu/hr	7,000	9,000	12,000	15,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	1250/1050/950/850/750	1250/1050/950/850/750	1250/1100/1000/900/750	1400/1350/1100/850/610	1250/1150/1050/950/800	1300/1200/1050/900/750
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	1200/1020/895/770/700	1200/1020/895/770/700	1200/1020/920/820/700	1400/1350/1200/1050/610	1250/1150/1025/900/750	1300/1200/1050/900/750
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	360/290/260/230/210	360/290/260/230/210	360/300/272/240/210	410/370/280/210/170	570/520/480/420/330	800/730/630/535/440
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	350/290/250/220/200	350/290/250/220/200	350/290/260/230/200	420/390/350/310/180	570/520/450/380/310	800/730/630/535/440
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/38/35/32/27	44/38/35/32/27	44/39/36/33/27	46/45/40/33/26	50/46/44/40/35	54/50/47/44/38
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/36/32/28/26	42/36/32/28/26	42/36/32/29/26	44/43/40/37/23	48/46/41/38/33	54/50/47/44/38
Auto Up-Down Louver	Yes	Yes	Yes	Yes	Yes	Yes
Auto Left-Right Louver	No	No	No	No	No	No
Dimension: H x W x D in (mm)	11 7/8 x 34 1/4 x 7 3/4 (301 x 870 x 196)	11 7/8 x 34 1/4 x 7 3/4 (301 x 870 x 196)	11 7/8 x 34 1/4 x 7 3/4 (301 x 870 x 196)	12 1/4 x 36 1/8 x 8 3/8 (312 x 918 x 213)	12 7/8 x 39 3/8 x 8 3/4 (327 x 999 x 223)	13 1/2 x 44 1/2 x 9 1/8 (343 x 1129 x 232)
Weight (Net/Ship) - lbs (kg)	21.62/26.7 (9.8/12.1)	21.84/26.92 (9.9/12.2)	21.84/26.92 (9.9/12.2)	24.49/30.45 (11.1/13.8)	27.8/34.64 (12.6/15.7)	34.86/43.03 (15.8/19.5)
Liquid O.D. in	1/4	1/4	1/4	1/4	1/4	1/4
Suction O.D. in	3/8	3/8	3/8	3/8	1/2	1/2
Drain Pipe Size O.D. in	5/8	5/8	5/8	5/8	5/8	5/8
WiFi*	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No	No	No	No
Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE INDOOR UNIT SPECIFICATIONS

PREMIUM HIGHWALL




EASIER TO: DO THE JOB



EXTENDED KICKSTAND

The built-in bracket provides extra room for easier installation and service.



MOUNTING TEMPLATE/PLATE

A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.



2-WAY PIPING DRAIN

Flexible right or left side condensation drain options simplify installation.



EASY-ACCESS PCB

The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.

EASIER TO: CLOSE THE SALE



WARM START

Ensures the fan does not blow cold air during heating mode startup.




TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



INDOOR AIR FILTER

The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.



3-D AIRFLOW

Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.



SMART SENSOR

Automatically changes to an energy-saving temperature while you are away, then back to your regular setting when you return.



FOLLOW & SURROUND

Allows the user to choose if the air is directed towards them (follow) or away from them (surround).

	GS09WP2BEA	GS12WP2BEA	GS18WP2BEA	GS24WP2BEA
Rated Capacity Btu/hr	9,000	12,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	1200/1100/875/650/610	1300/1250/1050/850/610	1300/1250/1050/850/800	1300/1200/1050/900/750
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	1200/1100/900/700/610	1300/1250/1150/1050/610	1300/1250/1025/800/750	1300/1200/1050/900/750
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	395/355/310/260/170	410/370/280/210/170	580/530/480/400/350	800/730/630/535/440
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	395/355/290/220/170	420/390/350/310/180	580/530/450/350/320	800/730/630/535/440
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/42/36/32/27	46/44/38/32/25	51/50/44/37/25	54/50/47/44/38
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/41/37/32/29	43/42/39/36/25	49/47/40/35/26	54/50/47/44/38
Auto Up-Down Louver	Yes	Yes	Yes	Yes
Auto Left-Right Louver	Yes	Yes	Yes	Yes
Dimension: H x W x D in (mm)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 7/8 x 39 3/4 x 8 3/4 (327 x 1009 x 223)	13 1/2 x 44 1/2 x 9 1/8 (343 x 1129 x 232)
Weight (Net/Ship)- lbs (kg)	24.49/30.56 (11.1/13.85)	24.49/30.56 (11.1/13.85)	29.57/36.63 (13.4/16.6)	34.86/43.03 (15.8/19.5)
Liquid O.D. in	1/4	1/4	1/4	1/4
Suction O.D. in	3/8	3/8	1/2	1/2
Drain Pipe Size O.D in	5/8	5/8	5/8	5/8
WiFi*	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No	No
Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE INDOOR UNIT SPECIFICATIONS

PREMIUM HIGHWALL

with Built-In Refrigerant Detection Sensor (RDS)




EASIER TO: DO THE JOB



EXTENDED KICKSTAND

The built-in bracket provides extra room for easier installation and service.



MOUNTING TEMPLATE/PLATE

A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.



2-WAY PIPING DRAIN

Flexible right or left side condensation drain options simplify installation.



EASY-ACCESS PCB

The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.

EASIER TO: CLOSE THE SALE



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



INDOOR AIR FILTER

The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.



3-D AIRFLOW

Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.



SMART SENSOR

Automatically changes to an energy-saving temperature while you are away, then back to your regular setting when you return.



FOLLOW & SURROUND

Allows the user to choose if the air is directed towards them (follow) or away from them (surround).

	GS06WP2BEA	GS09WP2BEB	GS12WP2BEB	GS18WP2BEB	GS24WP2BEB
Rated Capacity Btu/hr	6,000	9,000	12,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	1200/1100/1000/900/800	1200/1100/875/650/610	1300/1250/1050/850/610	1300/1250/1050/850/800	1300/1200/1050/900/750
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	1200/1100/1000/900/850	1200/1100/900/700/610	1300/1250/1150/1050/610	1300/1250/1025/800/750	1300/1200/1050/900/750
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	280/245/215/190/155	395/355/310/260/170	410/370/280/210/170	580/530/480/400/350	800/730/630/535/440
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	300/265/235/200/190	395/355/290/220/170	420/390/350/310/180	580/530/450/350/320	800/730/630/535/440
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/38/35/32/27	44/42/36/32/27	46/44/38/32/25	51/50/44/37/25	54/50/47/44/38
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/36/32/28/26	43/41/37/32/29	43/42/39/36/25	49/47/40/35/26	54/50/47/44/38
Auto Up-Down Louver	Yes	Yes	Yes	Yes	Yes
Auto Left-Right Louver	Yes	Yes	Yes	Yes	Yes
Dimension: H x W x D in (mm)	10 1/2 x 28 3/8 x 7 1/2 (191 x 721 x 268)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 7/8 x 39 3/4 x 8 3/4 (327 x 1009 x 223)	13 1/2 x 44 1/2 x 9 1/8 (343 x 1129 x 232)
Weight (Net/Ship)- lbs (kg)	16.8/20.7 (7.6/9.4)	24.49/30.56 (11.1/13.85)	24.49/30.56 (11.1/13.85)	29.57/36.63 (13.4/16.6)	34.86/43.03 (15.8/19.5)
Liquid O.D. in	1/4	1/4	1/4	1/4	1/4
Suction O.D. in	3/8	3/8	3/8	1/2	1/2
Drain Pipe Size O.D in	5/8	5/8	5/8	5/8	5/8
WiFi*	Built-in	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes	Yes	Yes

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE INDOOR UNIT SPECIFICATIONS

ONE-WAY CASSETTE



EASIER TO: DO THE JOB



CONVENIENT MODERN DESIGN

Flexible installation accommodates ceilings of various heights, and the sleek, recessed design fits between 16" ceiling joists for easy installation.



EASY-ACCESS PCB

The PCB and motor can be easily removed for quick component and wiring checks.



CONDENSATE PUMP

Factory-installed condensate pump with up to 27" lift height.



FRESH AIR KNOCKOUT

Unit designed with a 3" fresh air knockout.

EASIER TO: CLOSE THE SALE



WARM START

Ensures the fan does not blow cold air during heating mode startup.




TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



INDOOR AIR FILTER

The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.



3-D AIRFLOW

Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.



SMART SENSOR

Automatically changes to an energy-saving temperature while you are away, then back to your regular setting when you return.



ROOM TEMPERATURE DISPLAY

Easy-to-read dual seven segment display on the front of the panel.

	US07AB2BEA	US09AB2BEA	US12AB2BEA	US18AB2BEA
Panel Model	GAABP0718A	GAABP0718A	GAABP0718A	GAABP0718A
Rated Capacity Btu/hr	7,000	9,000	12,000	18,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	1200/1100/1000/900/800	1200/1100/1000/900/800	1250/1150/1050/950/850	1350/1230/1130/1030/930
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	1200/1100/1025/950/850	1200/1100/1025/950/850	1300/1250/1150/1050/950	1400/1330/1230/1130/1030
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	365/325/285/245/205	365/325/285/245/205	375/335/295/255/215	415/370/330/290/250
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	385/345/310/280/240	385/345/310/280/240	415/400/360/320/280	440/420/390/355/315
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	41/39/36/32/30	41/39/36/32/30	43/42/40/37/36	44/43/42/39/36
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	41/39/36/32/30	41/39/36/32/30	43/42/40/37/36	44/43/42/39/36
Chassis Dimension: HxWxD in (mm)	7 1/4 x 50 1/4 x 13 1/8 (185 x 1277 x 335)	7 1/4 x 50 1/4 x 13 1/8 (185 x 1277 x 335)	7 1/4 x 50 1/4 x 13 1/8 (185 x 1277 x 335)	7 1/4 x 50 1/4 x 13 1/8 (185 x 1277 x 335)
Panel Dimension: HxWxD in (mm)	3 1/8 x 54 1/2 x 18 5/8 (79 x 1358 x 473)	3 1/8 x 54 1/2 x 18 5/8 (79 x 1358 x 473)	3 1/8 x 54 1/2 x 18 5/8 (79 x 1358 x 473)	3 1/8 x 54 1/2 x 18 5/8 (79 x 1358 x 473)
Weight (Net/Ship)- lbs (kg)	41.4/76.7 (18.8/34.8)	41.4/76.7 (18.8/34.8)	42.1/78.9 (19.1/35.8)	42.1/78.9 (19.1/35.8)
Liquid Pipe O.D. (in)	1/4	1/4	1/4	1/4
Suction Pipe O.D. (in)	3/8	3/8	3/8	1/2
Drainpipe Size O.D. (in)	1*	1*	1*	1*
Condensate Pump Built-In	Yes	Yes	Yes	Yes
Max. Drain-Lift Height in (mm)	27 (686)	27 (686)	27 (686)	27 (686)
WiFi**	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No	No
Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.


**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE INDOOR UNIT SPECIFICATIONS

4-WAY CASSETTE



EASIER TO: DO THE JOB



COMPACT DESIGN

Fits 2' x 2' drop ceiling for easy installation (9-18K models).



CONDENSATE PUMP

Factory-installed condensate pump.



FRESH AIR KNOCKOUT

Unit designed with a 4" round fresh air knockout.

EASIER TO: CLOSE THE SALE



WARM START

Ensures the fan does not blow cold air during heating mode startup.



INDEPENDENT LOUVER CONTROL

The four cassette louvers can be set to the same, or different positions, to control airflow direction.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.

	US09CB2BEA	US12CB2BEA	US18CB2BEA	US24LB2BEA
Panel Model	GACCP01GA	GACCP01GA	GACCP01GA	GALCP01GA
Rated Capacity Btu/hr	9,000	12,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	830/760/690/620/560	830/760/690/620/560	850/800/760/680/590	620/580/540/430/360
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	830/760/690/620/560	830/760/690/620/560	850/800/760/680/590	620/580/540/430/360
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	458/425/387/345/302	1033/873/858/640/400
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	479/441/387/345/302	1033/873/858/640/400
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32	46/44/41/38/35
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32	46/44/42/39/36
Chassis Dimension: HxWxD in (mm)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	9 3/4 x 33 x 33 (248 x 840 x 840)
Panel Dimension: HxWxD in (mm)	2 3/8 x 27 7/16 x 27 7/16 (60 x 620 x 620)	2 3/8 x 27 7/16 x 27 7/16 (60 x 620 x 620)	2 3/8 x 27 7/16 x 27 7/16 (60 x 620 x 620)	1 15/16 x 37 3/8 x 37 3/8 (50 x 950 x 950)
Weight (Net/Ship)- lbs (kg)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)	56.22/85.32 (25.5/38.7)
Liquid Pipe O.D. (in)	1/4	1/4	1/4	3/8
Suction Pipe O.D. (in)	3/8	3/8	1/2	5/8
Drainpipe Size O.D. (in)	1*	1*	1*	1*
Condensate Pump Built-In	Yes	Yes	Yes	Yes
Max. Drain-Lift Height in (mm)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)
WiFi**	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No	No
Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE INDOOR UNIT SPECIFICATIONS

CONSOLE

with Built-In Refrigerant Detection Sensor (RDS)



EASIER TO: DO THE JOB



AIRFLOW DIRECTION CONTROL

Allows the homeowner to select preferred airflow direction - the top and bottom or top only.



INSTALLATION FLEXIBILITY

Unit can be placed on the floor or installed low on the wall.

EASIER TO: CLOSE THE SALE



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



ROOM TEMPERATURE DISPLAY

Easy-to-read dual seven segment display on the front of the panel.

	US09FB2BEA	US12FB2BEA	US18FB2BEA
Rated Capacity Btu/hr	9,000	12,000	18,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	700/560/480/410/360	800/590/510/440/390	850/710/690/560/510
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	700/560/480/410/360	800/590/510/440/390	850/710/690/560/510
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	290/218/205/176/147	314/226/210/195/175	345/341/271/218/210
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	312/206/205/176/147	311/223/200/195/175	345/300/280/218/210
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/40/37/32/24	47/41/37/33/25	49/44/43/40/37
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/37/32/27/20	47/40/37/33/25	49/43/43/37/37
Dimension: HxWxD in (mm)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)
Weight (Net/Ship)- lbs (kg)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)
Liquid Pipe O.D. (in)	1/4	1/4	1/4
Suction Pipe O.D. (in)	3/8	3/8	1/2
Drainpipe Size O.D. in	5/8	5/8	5/8
WiFi*	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE INDOOR UNIT SPECIFICATIONS

MID-STATIC DUCTED with Built-In Refrigerant Detection Sensor (RDS)



AUXILIARY HEATER COMPATIBLE

Compatible with many third-party auxiliary heaters.



FRESH AIR KNOCKOUT

Unit designed with a 4" round fresh air knockout.

EASIER TO: DO THE JOB



COMPACT DESIGN

Less than 10" height saves ceiling space.



CONDENSATE PUMP

Factory-installed condensate pump.



0.6" EXTERNAL STATIC

Designed for static pressure up to 0.6" w.g.

EASIER TO: CLOSE THE SALE



WARM START

Ensures the fan does not blow cold air during heating mode startup.



OPTIONAL ACCESSORIES

MERV filter box and supply plenums available (sold separately) for easy installation.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.

	US07MB2BEA	US09MB2BEA	US12MB2BEA	US18MB2BEA	US24MB2BEA
Rated Cooling Capacity Btu/hr	7,000	9,000	12,000	18,000	24,000
Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	830/780/700/640/560	880/800/720/640/560	950/870/780/680/600	880/820/760/700/640	1070/1030/880/790/740
Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	830/780/700/640/560	880/800/720/640/560	950/870/780/680/600	880/820/760/700/640	1070/1030/880/790/740
Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	335/272/190/150/141	353/286/200/150/141	409/350/308/158/148	620/517/332/214/203	927/844/667/564/482
Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	335/272/190/150/141	358/292/208/155/145	412/355/311/163/152	627/523/337/217/205	927/844/667/564/482
Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	42/39/37/35/32	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36	47/46/41/38/37
Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/39/37/35/32	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36	46/45/40/38/36
Dimension: HxWxD in (mm)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 47 1/2 x 27 1/2 (248 x 1207 x 700)	9 3/4 x 47 1/2 x 27 1/2 (248 x 1207 x 700)
Weight (Net/Ship) - lbs (kg)	62.17/86.86 (28.2/39.4)	62.17/86.86 (28.2/39.4)	62.17/86.86 (28.2/39.4)	87.74/123.46 (39.8/56)	87.74/123.46 (39.8/56)
Max. External Static Pressure in.W.G (Pa)	0.6 (150)	0.6 (150)	0.6 (150)	0.6 (150)	0.6 (150)
Liquid Pipe O.D. (in)	1/4	1/4	1/4	1/4	3/8
Suction Pipe O.D. (in)	3/8	3/8	3/8	1/2	5/8
Drainpipe Size	1*	1*	1*	1*	1*
Condensate Pump Built-In	Yes	Yes	Yes	Yes	Yes
Max. Drain-Lift Height in(mm)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)
WiFi**	Built-in	Built-in	Built-in	Built-in	Built-in
Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes	Yes	Yes

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

MULTI-ZONE CAPACITY COMBINATION MATRIX

PIPING ADAPTER GUIDE

■ 6-15K MODELS

- These units use 1/4" liquid and 3/8" vapor lines.
- Check the multi-zone unit for a port that matches these sizes.
- If an adapter is required, install on the outdoor unit port side.

ODU Port Size	Adapter	Description	Part Number
1/4" & 3/8"	None	Direct Connection	-
1/4" & 1/2"	E	1/2" to 3/8" (vapor line)	WJ01X26854

■ ALL 18K MODELS & 24K HIGHWALL MODELS (GS24WB2BE**/GS24WP2BE**)

- These units use 1/4" liquid and 1/2" vapor lines.
- Check the multi-zone unit for a port that matches these sizes.
- If an adapter is required, install on the outdoor unit port side.

ODU Port Size	Adapter	Description	Part Number
1/4" & 1/2"	None	Direct Connection	-
1/4" & 3/8"	D	3/8" to 1/2" (vapor line)	WJ01X26853


■ 24K CASSETTE/DUCTED (US24LB2BE**/US24MB2BE**)

- These units use 3/8" liquid and 5/8" vapor lines.
- No multi-zone ports match these sizes directly.
- Adapters are required - install on the outdoor unit port side.

ODU Port Size	Adapter	Description	Part Number
1/4" & 3/8"	A	1/4" to 3/8" (liquid line)	WJ01X23925
	B	3/8" to 5/8" (vapor line)	WJ01X23924
1/4" & 1/2"	A	1/4" to 3/8" (liquid line)	WJ01X23925
	C	1/2" to 5/8" (vapor line)	WJ01X23932

QUICK TIPS

- Always check port sizes first before installing.
- Use adapters only on the outdoor unit side.
- Label adapters if needed to avoid confusion during service.
- Keep common adapters in your kit for faster installs.




2G18AD2BE** 2G20ED2BE**

- No adapters required
- Port Sizes:
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

Combinations

		Ports					
		B	A	B	A	B	A
Two-Zone	9K	9K	9K	9K	15K	6K	
	12K	6K	12K	6K	15K	7K	
	12K	7K	12K	7K	15K	9K	
	12K	9K	12K	9K			
	12K	12K	12K	12K			



3G24AD2BE** 3G24ED2BE**

- Ships with adapter D
- No adapters required for Ports B, A
- Port Sizes:
 - » Port C :1/4" x 3/8"
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

Combinations

		Ports											
		C	B	A	C	B	A	C	B	A	C	B	A
Two-Zone	6K	6K	-	12K	6K	-	15K	9K	-	18K	12K	-	
	7K	6K	-	12K	7K	-	15K	12K	-	24K	6K	-	
	7K	7K	-	12K	9K	-	15K	15K	-	24K	7K	-	
	9K	6K	-	12K	12K	-	18K	6K	-	24K	9K	-	
	9K	7K	-	15K	6K	-	18K	7K	-				
	9K	9K	-	15K	7K	-	18K	9K	-				
Three-Zone	6K	6K	6K	9K	9K	6K	12K	9K	7K	15K	7K	7K	
	7K	6K	6K	9K	9K	7K	12K	9K	9K	15K	9K	6K	
	7K	7K	6K	9K	9K	9K	12K	12K	6K	15K	9K	7K	
	7K	7K	7K	12K	6K	6K	12K	12K	7K	15K	9K	9K	
	9K	6K	6K	12K	7K	6K	12K	12K	9K	18K	6K	6K	
	9K	7K	6K	12K	7K	7K	15K	6K	6K	18K	7K	6K	
	9K	7K	7K	12K	9K	6K	15K	7K	6K	18K	7K	7K	



4G36AD2BE**
4G36ED2BE**

- Ships with adapters D and E
- No adapters required for Ports B, A
- Port Sizes:
 - » Port D: 1/4" x 1/2"
 - » Port C: 1/4" x 3/8"
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

Combinations

		Ports															
		D	C	B	A	D	C	B	A	D	C	B	A	D	C	B	A
Two-Zone		18K	9K	-	-	18K	18K	-	-	24K	7K	-	-	24K	15K	-	-
		18K	12K	-	-	18K	24K	-	-	24K	9K	-	-	24K	24K	-	-
		18K	15K	-	-	24K	6K	-	-	24K	12K	-	-				
Three-Zone		-	9K	9K	9K	-	15K	12K	6K	18K	9K	9K	-	24K	6K	6K	-
		-	12K	9K	6K	-	15K	12K	7K	18K	12K	6K	-	24K	7K	6K	-
		-	12K	9K	7K	-	15K	12K	9K	18K	12K	7K	-	24K	7K	7K	-
		-	12K	9K	9K	-	15K	12K	12K	18K	12K	9K	-	24K	9K	6K	-
		-	12K	12K	6K	-	15K	15K	6K	18K	12K	12K	-	24K	9K	7K	-
		-	12K	12K	7K	-	15K	15K	7K	18K	15K	6K	-	24K	9K	9K	-
		-	12K	12K	9K	-	15K	15K	9K	18K	15K	7K	-	24K	12K	6K	-
		-	12K	12K	12K	-	15K	15K	12K	18K	15K	9K	-	24K	12K	7K	-
		-	15K	6K	6K	-	15K	15K	15K	18K	15K	12K	-	24K	12K	9K	-
		-	15K	7K	6K	18K	6K	6K	-	18K	15K	15K	-	24K	12K	12K	-
		-	15K	7K	7K	18K	7K	6K	-	18K	18K	6K	-	24K	15K	6K	-
		-	15K	9K	6K	18K	7K	7K	-	18K	18K	7K	-	24K	15K	7K	-
		-	15K	9K	7K	18K	9K	6K	-	18K	18K	9K	-	24K	15K	9K	-
		-	15K	9K	9K	18K	9K	7K	-	18K	18K	12K	-				
Four-Zone		6K	6K	6K	6K	12K	9K	9K	6K	15K	9K	9K	9K	18K	9K	7K	6K
		7K	6K	6K	6K	12K	9K	9K	7K	15K	12K	6K	6K	18K	9K	7K	7K
		7K	7K	6K	6K	12K	9K	9K	9K	15K	12K	7K	6K	18K	9K	9K	6K
		7K	7K	7K	6K	12K	12K	6K	6K	15K	12K	7K	7K	18K	9K	9K	7K
		7K	7K	7K	7K	12K	12K	7K	6K	15K	12K	9K	6K	18K	9K	9K	9K
		9K	6K	6K	6K	12K	12K	7K	7K	15K	12K	9K	7K	18K	12K	6K	6K
		9K	7K	6K	6K	12K	12K	9K	6K	15K	12K	9K	9K	18K	12K	7K	6K
		9K	7K	7K	6K	12K	12K	9K	7K	15K	12K	12K	6K	18K	12K	7K	7K
		9K	7K	7K	7K	12K	12K	9K	9K	15K	12K	12K	7K	18K	12K	9K	6K
		9K	9K	6K	6K	12K	12K	12K	6K	15K	12K	12K	9K	18K	12K	9K	7K
		9K	9K	7K	6K	12K	12K	12K	7K	15K	12K	12K	12K	18K	12K	9K	9K
		9K	9K	7K	7K	12K	12K	12K	9K	15K	15K	6K	6K	18K	15K	6K	6K
		9K	9K	9K	6K	12K	12K	12K	12K	15K	15K	7K	6K	18K	15K	7K	6K
		9K	9K	9K	7K	15K	6K	6K	6K	15K	15K	7K	7K	18K	15K	7K	7K
		9K	9K	9K	9K	15K	7K	6K	6K	15K	15K	9K	6K	18K	15K	9K	6K
		12K	6K	6K	6K	15K	7K	7K	6K	15K	15K	9K	7K	24K	6K	6K	6K
		12K	7K	6K	6K	15K	7K	7K	7K	15K	15K	9K	9K	24K	7K	6K	6K
		12K	7K	7K	6K	15K	9K	6K	6K	18K	6K	6K	6K	24K	7K	7K	6K
		12K	7K	7K	7K	15K	9K	7K	6K	18K	7K	6K	6K	24K	7K	7K	7K
		12K	9K	6K	6K	15K	9K	7K	7K	18K	7K	7K	6K	24K	9K	6K	6K
		12K	9K	7K	6K	15K	9K	9K	6K	18K	7K	7K	7K	24K	9K	7K	6K
		12K	9K	7K	7K	15K	9K	9K	7K	18K	9K	6K	6K	24K	9K	7K	7K

MULTI-ZONE CAPACITY COMBINATION MATRIX



5G42ED2BE**

- Ships with (2) adapter E
- No adapters required for Ports B, A
- Port Sizes:
 - » Port E: 1/4" x 1/2"
 - » Port D: 1/4" x 1/2"
 - » Port C: 1/4" x 3/8"
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

SEE
PIPING ADAPTER
GUIDE
ON PREVIOUS PAGE

Combinations

		Ports																			
		E	D	C	B	A	E	D	C	B	A	E	D	C	B	A	E	D	C	B	A
Two-Zone	18K	-	9K	-	-	18K	18K	-	-	-	24K	-	9K	-	-	24K	18K	-	-	-	
	18K	-	12K	-	-	24K	-	6K	-	-	24K	-	12K	-	-	24K	24K	-	-	-	
	18K	-	15K	-	-	24K	-	7K	-	-	24K	-	15K	-	-						
Three-Zone	-	-	9K	9K	9K	-	-	15K	12K	9K	18K	-	12K	12K	-	24K	-	9K	7K	-	
	-	-	12K	9K	6K	-	-	15K	12K	12K	18K	-	15K	6K	-	24K	-	9K	9K	-	
	-	-	12K	9K	7K	-	-	15K	15K	6K	18K	-	15K	7K	-	24K	-	12K	6K	-	
	-	-	12K	9K	9K	-	-	15K	15K	7K	18K	-	15K	9K	-	24K	-	12K	7K	-	
	-	-	12K	12K	6K	-	-	15K	15K	9K	18K	-	15K	12K	-	24K	-	12K	9K	-	
	-	-	12K	12K	7K	-	-	15K	15K	12K	18K	-	15K	15K	-	24K	-	12K	12K	-	
	-	-	12K	12K	9K	-	-	15K	15K	15K	18K	18K	6K	-	-	24K	-	15K	6K	-	
	-	-	12K	12K	12K	18K	-	6K	6K	-	18K	18K	7K	-	-	24K	-	15K	7K	-	
	-	-	15K	6K	6K	18K	-	7K	6K	-	18K	18K	9K	-	-	24K	-	15K	9K	-	
	-	-	15K	7K	6K	18K	-	7K	7K	-	18K	18K	12K	-	-	24K	-	15K	12K	-	
	-	-	15K	7K	7K	18K	-	9K	6K	-	18K	18K	15K	-	-	24K	-	15K	15K	-	
	-	-	15K	9K	6K	18K	-	9K	7K	-	18K	18K	18K	-	-	24K	18K	6K	-	-	
	-	-	15K	9K	7K	18K	-	9K	9K	-	24K	-	6K	6K	-	24K	18K	7K	-	-	
	-	-	15K	9K	9K	18K	-	12K	6K	-	24K	-	7K	6K	-	24K	18K	9K	-	-	
	-	-	15K	12K	6K	18K	-	12K	7K	-	24K	-	7K	7K	-	24K	18K	12K	-	-	
	-	-	15K	12K	7K	18K	-	12K	9K	-	24K	-	9K	6K	-	24K	18K	15K	-	-	
Four-Zone	6K	-	6K	6K	6K	12K	-	12K	12K	9K	18K	-	7K	6K	6K	18K	18K	9K	6K	-	
	7K	-	6K	6K	6K	12K	-	12K	12K	12K	18K	-	7K	7K	6K	18K	18K	9K	7K	-	
	7K	-	7K	6K	6K	15K	-	6K	6K	6K	18K	-	7K	7K	7K	18K	18K	9K	9K	-	
	7K	-	7K	7K	7K	15K	-	7K	6K	6K	18K	-	9K	6K	6K	18K	18K	12K	6K	-	
	9K	-	6K	6K	6K	15K	-	7K	7K	6K	18K	-	9K	7K	6K	18K	18K	12K	7K	-	
	9K	-	7K	6K	6K	15K	-	7K	7K	7K	18K	-	9K	7K	7K	18K	18K	12K	9K	-	
	9K	-	7K	7K	6K	15K	-	9K	6K	6K	18K	-	9K	9K	6K	24K	-	6K	6K	6K	
	9K	-	7K	7K	7K	15K	-	9K	7K	6K	18K	-	9K	9K	7K	24K	-	7K	6K	6K	
	9K	-	9K	6K	6K	15K	-	9K	7K	7K	18K	-	9K	9K	9K	24K	-	7K	7K	6K	
	9K	-	9K	7K	6K	15K	-	9K	9K	6K	18K	-	12K	6K	6K	24K	-	7K	7K	7K	
	9K	-	9K	7K	7K	15K	-	9K	9K	7K	18K	-	12K	7K	6K	24K	-	9K	6K	6K	
	9K	-	9K	9K	6K	15K	-	9K	9K	9K	18K	-	12K	7K	7K	24K	-	9K	7K	6K	
	9K	-	9K	9K	7K	15K	-	12K	6K	6K	18K	-	12K	9K	6K	24K	-	9K	7K	7K	
	9K	-	9K	9K	9K	15K	-	12K	7K	6K	18K	-	12K	9K	7K	24K	-	9K	9K	6K	
	12K	-	6K	6K	6K	15K	-	12K	7K	7K	18K	-	12K	9K	9K	24K	-	9K	9K	7K	
	12K	-	7K	6K	6K	15K	-	12K	9K	6K	18K	-	12K	12K	6K	24K	-	9K	9K	9K	
	12K	-	7K	7K	6K	15K	-	12K	9K	7K	18K	-	12K	12K	7K	24K	-	12K	6K	6K	
	12K	-	7K	7K	7K	15K	-	12K	9K	9K	18K	-	12K	12K	9K	24K	-	12K	7K	6K	
	12K	-	9K	6K	6K	15K	-	12K	12K	6K	18K	-	12K	12K	12K	24K	-	12K	7K	7K	
	12K	-	9K	7K	6K	15K	-	12K	12K	7K	18K	-	15K	6K	6K	24K	-	12K	9K	6K	
	12K	-	9K	7K	7K	15K	-	12K	12K	9K	18K	-	15K	7K	6K	24K	-	12K	9K	7K	
	12K	-	9K	9K	6K	15K	-	12K	12K	12K	18K	-	15K	7K	7K	24K	-	12K	9K	9K	
	12K	-	9K	9K	7K	15K	-	15K	6K	6K	18K	-	15K	9K	6K	24K	-	12K	12K	6K	
	12K	-	9K	9K	9K	15K	-	15K	7K	6K	18K	-	15K	9K	7K	24K	-	12K	12K	7K	
	12K	-	12K	6K	6K	15K	-	15K	7K	7K	18K	-	15K	9K	9K	24K	-	15K	6K	6K	
	12K	-	12K	7K	6K	15K	-	15K	9K	6K	18K	-	15K	12K	6K	24K	-	15K	7K	6K	
	12K	-	12K	7K	7K	15K	-	15K	9K	7K	18K	-	15K	12K	7K	24K	-	15K	7K	7K	
	12K	-	12K	9K	6K	15K	-	15K	9K	9K	18K	-	15K	12K	9K	24K	-	15K	9K	6K	
	12K	-	12K	9K	7K	15K	-	15K	12K	9K	18K	-	15K	12K	12K	24K	-	15K	9K	7K	
	12K	-	12K	9K	9K	15K	-	15K	12K	12K	18K	18K	6K	6K	-	24K	18K	6K	6K	-	
	12K	-	12K	12K	6K	15K	-	15K	15K	12K	18K	18K	7K	6K	-	24K	18K	7K	6K	-	
	12K	-	12K	12K	7K	18K	-	6K	6K	6K	18K	18K	7K	7K	-	24K	18K	7K	7K	-	

Combinations (Continued)

	Ports																			
	E	D	C	B	A	E	D	C	B	A	E	D	C	B	A	E	D	C	B	A
Five-Zone	6K	6K	6K	6K	6K	12K	12K	12K	6K	6K	15K	15K	7K	7K	6K	18K	12K	12K	9K	6K
	7K	6K	6K	6K	6K	12K	12K	12K	7K	6K	15K	15K	7K	7K	7K	18K	12K	12K	9K	7K
	7K	7K	6K	6K	6K	12K	12K	12K	7K	7K	15K	15K	9K	6K	6K	18K	12K	12K	9K	9K
	7K	7K	7K	6K	6K	12K	12K	12K	9K	6K	15K	15K	9K	7K	6K	18K	15K	6K	6K	6K
	7K	7K	7K	7K	6K	12K	12K	12K	9K	7K	15K	15K	9K	7K	7K	18K	15K	7K	6K	6K
	7K	7K	7K	7K	7K	12K	12K	12K	9K	9K	15K	15K	9K	9K	6K	18K	15K	7K	7K	6K
	9K	6K	6K	6K	6K	12K	12K	12K	12K	6K	15K	15K	9K	9K	7K	18K	15K	7K	7K	7K
	9K	7K	6K	6K	6K	12K	12K	12K	12K	7K	15K	15K	9K	9K	9K	18K	15K	9K	6K	6K
	9K	7K	7K	6K	6K	12K	12K	12K	12K	9K	15K	15K	12K	6K	6K	18K	15K	9K	7K	6K
	9K	7K	7K	7K	6K	12K	12K	12K	12K	12K	15K	15K	12K	7K	6K	18K	15K	9K	7K	7K
	9K	7K	7K	7K	7K	15K	6K	6K	6K	6K	15K	15K	12K	7K	7K	18K	15K	9K	9K	6K
	9K	9K	6K	6K	6K	15K	7K	6K	6K	6K	15K	15K	12K	9K	6K	18K	15K	9K	9K	7K
	9K	9K	7K	6K	6K	15K	7K	7K	6K	6K	15K	15K	12K	9K	7K	18K	15K	9K	9K	9K
	9K	9K	7K	7K	6K	15K	7K	7K	7K	6K	15K	15K	12K	9K	9K	18K	15K	12K	6K	6K
	9K	9K	7K	7K	7K	15K	7K	7K	7K	7K	15K	15K	15K	6K	6K	18K	15K	12K	7K	6K
	9K	9K	9K	6K	6K	15K	9K	6K	6K	6K	15K	15K	15K	7K	6K	18K	15K	12K	7K	7K
	9K	9K	9K	7K	6K	15K	9K	7K	6K	6K	15K	15K	15K	7K	7K	18K	15K	12K	9K	6K
	9K	9K	9K	7K	7K	15K	9K	7K	7K	6K	15K	15K	15K	9K	6K	24K	6K	6K	6K	6K
	9K	9K	9K	9K	6K	15K	9K	7K	7K	7K	18K	6K	6K	6K	6K	24K	7K	6K	6K	6K
	9K	9K	9K	9K	7K	15K	9K	9K	6K	6K	18K	7K	6K	6K	6K	24K	7K	7K	6K	6K
	9K	9K	9K	9K	9K	15K	9K	9K	7K	6K	18K	7K	7K	6K	6K	24K	7K	7K	7K	6K
	12K	6K	6K	6K	6K	15K	9K	9K	7K	7K	18K	7K	7K	7K	6K	24K	7K	7K	7K	7K
	12K	7K	6K	6K	6K	15K	9K	9K	9K	6K	18K	7K	7K	7K	7K	24K	9K	6K	6K	6K
	12K	7K	7K	6K	6K	15K	9K	9K	9K	7K	18K	9K	6K	6K	6K	24K	9K	7K	6K	6K
	12K	7K	7K	7K	6K	15K	9K	9K	9K	9K	18K	9K	7K	6K	6K	24K	9K	7K	7K	6K
	12K	7K	7K	7K	7K	15K	12K	6K	6K	6K	18K	9K	7K	7K	6K	24K	9K	7K	7K	7K
	12K	9K	6K	6K	6K	15K	12K	7K	6K	6K	18K	9K	7K	7K	7K	24K	9K	9K	6K	6K
	12K	9K	7K	6K	6K	15K	12K	7K	7K	6K	18K	9K	9K	6K	6K	24K	9K	9K	7K	6K
	12K	9K	7K	7K	6K	15K	12K	7K	7K	7K	18K	9K	9K	7K	6K	24K	9K	9K	7K	7K
	12K	9K	7K	7K	7K	15K	12K	9K	6K	6K	18K	9K	9K	7K	7K	24K	9K	9K	9K	6K
	12K	9K	9K	6K	6K	15K	12K	9K	7K	6K	18K	9K	9K	9K	6K	24K	9K	9K	9K	7K
	12K	9K	9K	7K	6K	15K	12K	9K	7K	7K	18K	9K	9K	9K	7K	24K	9K	9K	9K	9K
	12K	9K	9K	7K	7K	15K	12K	9K	9K	6K	18K	9K	9K	9K	9K	24K	12K	6K	6K	6K
	12K	9K	9K	9K	6K	15K	12K	9K	9K	7K	18K	12K	6K	6K	6K	24K	12K	7K	6K	6K
	12K	9K	9K	9K	7K	15K	12K	9K	9K	9K	18K	12K	7K	6K	6K	24K	12K	7K	7K	6K
	12K	9K	9K	9K	9K	15K	12K	12K	6K	6K	18K	12K	7K	7K	6K	24K	12K	7K	7K	7K
	12K	12K	6K	6K	6K	15K	12K	12K	7K	6K	18K	12K	7K	7K	7K	24K	12K	9K	6K	6K
	12K	12K	7K	6K	6K	15K	12K	12K	7K	7K	18K	12K	9K	6K	6K	24K	12K	9K	7K	6K
	12K	12K	7K	7K	6K	15K	12K	12K	9K	6K	18K	12K	9K	7K	6K	24K	12K	9K	7K	7K
	12K	12K	7K	7K	7K	15K	12K	12K	9K	7K	18K	12K	9K	7K	7K	24K	12K	9K	9K	6K
	12K	12K	9K	6K	6K	15K	12K	12K	9K	9K	18K	12K	9K	9K	6K	24K	15K	6K	6K	6K
	12K	12K	9K	7K	6K	15K	12K	12K	12K	6K	18K	12K	9K	9K	7K	24K	15K	7K	6K	6K
	12K	12K	9K	7K	7K	15K	12K	12K	12K	7K	18K	12K	9K	9K	9K	24K	15K	7K	7K	6K
	12K	12K	9K	9K	6K	15K	12K	12K	12K	9K	18K	12K	12K	6K	6K	24K	15K	7K	7K	7K
	12K	12K	9K	9K	7K	15K	15K	6K	6K	6K	18K	12K	12K	7K	6K	24K	15K	9K	6K	6K
	12K	12K	9K	9K	9K	15K	15K	7K	6K	6K	18K	12K	12K	7K	7K					



LIMITED WARRANTY

We take pride in our workmanship; our standard coverage includes a 5-year limited warranty on parts.

Additionally, our ductless systems qualify for a 10-year limited warranty on parts with registration. To receive the extended coverage, equipment must be registered within 60 days of installation. Please refer to the warranty documentation for complete details.



To register your equipment go to:
www.geappliancesairandwater.com/warranty



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

