

# ADA404REFAL



32" x 19.75" x 22.5" (H x W x D)

Built-in undercounter ADA compliant +2°C to +8°C commercially approved with lock, digital controls, wire shelving, hospital cord with 'green dot' plug, digital thermometer with alarm, and automatic defrost operation

**Highlights:**

Just 32" high for an easy fit under lower ADA compliant counters

Flexible design allows built-in or freestanding use in 20" wide spaces

External temperature readout of the current and high/low temperatures

**Product Features:**

|                              |                                                                                                                                                                                                                                                               |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADA compliant design         | 32" height allows easy installation under lower ADA compliant counters                                                                                                                                                                                        |
| Built-in capable             | Front-breathing design lets you make the best use of space by installing your appliance under the counter                                                                                                                                                     |
| +2°C to +8°C operation       | Designed to safely store vaccines, select pharmaceuticals, and other materials with strict temperature requirements                                                                                                                                           |
| External temperature readout | Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button                                                                                                         |
| Buffered temperature probe   | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the left wall of the inner cabinet. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines |
| 3" thick door                | Improved insulation for an efficient performance; NOTE: due to the oversized design, the door does not open in its own radius. If installing this freezer against a wall, please see our drawings to ensure adequate space                                    |
| Flat door liner              | Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials                                                                                                                                                                |
| High/low temperature alarm   | Audible alarm sounds if the interior temperature rises or falls out of set range                                                                                                                                                                              |

Open door alarm Audible alarm will sound if the door is left ajar for over a minute

## ADA404REFAL Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Nominal Height             | 32.0" (81 cm)      |
| Height of Cabinet          | 31.75" (81 cm)     |
| Height to Hinge Cap        | 32.0" (81 cm)      |
| Nominal Width              | 20.0" (51 cm)      |
| Width                      | 19.75" (50 cm)     |
| Width with Door Open       | 20.25" (51 cm)     |
| Nominal Depth              | 23.0" (58 cm)      |
| Depth                      | 22.5" (57 cm)      |
| Depth with Handle          | 24.38" (62 cm)     |
| Depth with door at 90°     | 40.25" (102 cm)    |
| Capacity                   | 3.32 cu.ft. (94 L) |
| Defrost Type               | Automatic          |
| Door                       | White              |
| Cabinet                    | White              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Amps                       | 1.1                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 59.0 lbs. (27 kg)  |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101079042       |
| Refrigerator Features      |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Shelf Type                 | Wire               |
| Shelf Qty                  | 4                  |
| Thermostat Type            | Digital            |
| Fan Type                   | Interior           |
| Refrigerant Type           | R600a              |
| Refrigerant Amount         | 0.99oz.            |
| High Side PSI              | 180.0              |
| Low Side PSI               | 80.0               |
| Level Legs Qty             | 2                  |
| Interior Light             | Yes                |
| Sound Level                | 2°C to 8°C         |
| Dimensions                 |                    |

|                        |                |
|------------------------|----------------|
| Interior Height        | 23.5" (60 cm)  |
| Interior Width         | 16.25" (41 cm) |
| Interior Depth         | 17.0" (43 cm)  |
| Compressor Step Height | 6.25" (16 cm)  |
| Compressor Step Width  | 16.25" (41 cm) |
| Compressor Step Depth  | 6.0" (15 cm)   |

