

# ARG1PV456



21.5" x 17.5" x 19.75" (H x W x D)

Performance series Pharma-Vac 1 cu.ft. glass door all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

**Highlights:**

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

**Product Features:**

Certified to NSF/ANSI 456 Vaccine Storage Standard    Designed and tested to comply with the new NSF Vaccine Storage Standard

|                                                 |                                                                                                                                                                                      |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Purpose-built design                            | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines                                                              |
| +/-1°C Variation                                | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Certificate of calibration included             | 2-year calibration certificate included for your records                                                                                                                             |
| Antimicrobial silver ion-coated handle          | Powder-coated handle with naturally occurring silver ions to help reduce germ spread                                                                                                 |
| Adjustable temperature                          | Intuitive controls let you adjust the interior temperature between +2 to +8°C                                                                                                        |
| Temperature alarm                               | Visual and audible alarms alert if the interior temperature rises or falls out of set range                                                                                          |
| Remote alarm contacts                           | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)                     |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup                                                                                         |

## ARG1PV456 Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Nominal Height             | 22.0" (56 cm)      |
| Height of Cabinet          | 21.5" (55 cm)      |
| Nominal Width              | 18.0" (46 cm)      |
| Width                      | 17.5" (44 cm)      |
| Width with Door Open       | 18.0" (46 cm)      |
| Nominal Depth              | 20.0" (51 cm)      |
| Depth                      | 19.75" (50 cm)     |
| Depth with Handle          | 21.5" (55 cm)      |
| Depth with door at 90°     | 36.0" (91 cm)      |
| Capacity                   | 1.0 cu.ft. (28 L)  |
| Defrost Type               | Automatic          |
| Door                       | Glass              |
| Cabinet                    | White              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S to NSF 456   |
| Amps                       | 0.6                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 63.0 lbs. (29 kg)  |
| Parts & Labor Warranty     | 2 Years            |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101090603       |
| Refrigerator Features      |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Shelf Type                 | Wire               |
| Shelf Qty                  | 3                  |
| Adjustable Shelves         | Yes                |
| Thermostat Type            | Digital            |
| Fan Type                   | Interior           |
| Refrigerant Type           | R600a              |
| Refrigerant Amount         | 0.71oz.            |
| Interior Light             | Yes                |
| Temperature Range          | 2 to 8°C           |
| Dimensions                 |                    |
| Interior Height            | 15.75" (40 cm)     |
| Interior Width             | 14.0" (36 cm)      |

Interior Depth

8.0"

