

ARS6MLMC



32.5" x 23.38" x 24.38" (H x W x D)

Purpose-built ADA height all-refrigerator for breast milk storage with 4 adjustable shelves, antimicrobial silver-ion handle, and hospital grade cord with 'green dot' plug

Highlights:

Designed for use in NICUs, hospitals, maternity wards, lactation rooms, mothers' suites, and other facilities

Purpose-built for environments complying with Section 4207 of the Patient Protection and Affordable Care Act

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

Product Features:

| | |
|--|--|
| Purpose-built design | Designed and purpose-built for breast milk storage |
| Antimicrobial silver ion-coated handle | Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between 33 to 40°F |
| Adjustable plastic-coated wire shelves | Multiple shelf positions spaced at ½" for improved air circulation and storage |
| Microprocessor control panel | Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management |
| Reversible door | User-friendly reversible door for increased flexibility |
| Factory-installed lock | Keyed locked near top of door for added security (2 keys included) |
| Access port (probe) | Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment |
| Remote alarm contacts | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |

ARS6MLMC Specifications:

| Overview | |
|----------------------------|--------------------|
| Nominal Height | 32.0" (81 cm) |
| Height of Cabinet | 32.5" (83 cm) |
| Nominal Width | 24.0" (61 cm) |
| Width | 23.38" (59 cm) |
| Width with Door Open | 23.88" (61 cm) |
| Nominal Depth | 25.0" (64 cm) |
| Depth | 24.38" (62 cm) |
| Depth with Handle | 26.13" (66 cm) |
| Depth with door at 90° | 46.5" (118 cm) |
| Capacity | 6.0 cu.ft. (170 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.4 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 120.0 lbs. (54 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101066622 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Yes |
| Shelf Type | Wire |
| Shelf Qty | 4 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 1.73oz. |
| Interior Light | Yes |
| Temperature Range | 33 to 40°F |
| Sound Level | 36.4 dB |
| Dimensions | |
| Interior Height | 24.5" (62 cm) |
| Interior Width | 20.0" (51 cm) |

| | |
|------------------------|---------------|
| Interior Depth | 17.0" (43 cm) |
| Compressor Step Height | 6.5" (17 cm) |
| Compressor Step Width | 20.0" (51 cm) |
| Compressor Step Depth | 5.0" (13 cm) |

