

ARS8PV-FS30LSTACKMED2



76.5" x 23.38" x 24.38" (H x W x D)

Stacked combination of ARS8PV all-refrigerator with antimicrobial silver-ion handle and hospital grade cord with 'green dot' plug and FS30LMED2 compact manual defrost all-freezer for vaccine storage

Highlights:

Independent refrigerator and freezer storage in one slim-fitting footprint for space-challenged facilities

Intelligent microprocessor digital temperature controller for optimum temperature management

ARS8PV refrigerator has a powder-coated handle with naturally occurring silver ions to help reduce germ spread

Product Features:

Space-saving design	Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint
ARS8PV all-refrigerator	8 cu.ft. automatic defrost all-refrigerator with digital controls, wire shelving, and keyed lock for added security
FS30LMED2 all-freezer	Compact manual defrost all-freezer with digital thermostat and wire shelving
Antimicrobial silver ion-coated handle (refrigerator)	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines
+/-1°C Variation (refrigerator)	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C (refrigerator) and -20° to -15°C (freezer)

Temperature alarms, FELIX STORCH, INC. | ISO 9001:2015 Certified | Visual and audible alarms alert if the interior temperature rises or falls out of set range

ARS8PV-FS30LSTACKMED2 Specifications:

Overview	
Nominal Height	77.0" (196 cm)
Height of Cabinet	76.5" (194 cm)
Nominal Width	24.0" (61 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Nominal Depth	25.0" (64 cm)
Depth	24.38" (62 cm)
Depth with Handle	26.13" (66 cm)
Depth with door at 90°	46.5" (118 cm)
Capacity	9.8 cu.ft. (278 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	2.2
Voltage/Frequency	115 V AC/60 Hz
Weight	204.0 lbs. (93 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101077659
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Interior Light	Yes
Refrigerator - Interior Height	41.25" (105 cm)
Refrigerator - Interior Width	20.0" (51 cm)
Refrigerator - Interior Depth	17.0" (43 cm)
Refrigerator - Capacity	8.0 cu.ft
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	7
Refrigerator - Temperature Range	2 to 8°C
Refrigerator - Refrigerant Type	R600a

Refrigerator - Refrigerant Amount	1.73 oz.
Freezer - Interior Height	18.5" (47 cm)
Freezer - Interior Width	13.5" (34 cm)
Freezer - Interior Depth	13.0" (33 cm)
Freezer - Capacity	1.8 cu.ft
Freezer - Shelf Type	Wire
Freezer - Shelf Qty	2
Thermostat Type	Digital
Fan Type	Interior
Freezer - Temperature Range	-20° to -15°C
Freezer - Refrigerant Type	R600a
Freezer - Refrigerant Amount	0.8 oz.

