




ASM22DB—GE Profile™ 230 Volt Window Room Air Conditioner with Electronic Remote Control


Wall Case Dimensions (in inches)



*Distance from front of case to side louvers (excluding grille).

Note: When installing slide-out chassis units in through-the-wall applications, keep louvers free. Do not restrict air flow areas.

Perpendicular



230/208V
20 Amp

Wall Outlets: All wiring, including installation of receptacle, must be made in accordance with local electrical codes and regulations. Electrical outlet should be in reach of line cord.

Note: Aluminum building wiring may pose special problems—consult a qualified electrician.

Specification Created 5/01

For answers to your Monogram®, GE Profile™ or GE appliance questions, visit our website at GEAppliances.com or call GE Answer Center® service, 800.626.2000.




Total capacity and E.E.R. ratings are calculated based on the Association of Home Appliance Manufacturers' standards.



Listed by
Underwriters
Laboratories



ASM22DB—GE Profile™ 230 Volt Window Room Air Conditioner with Electronic Remote Control



Features and Benefits

- 22,000 / 21,500 BTUH, 230 / 208 Volts
- 8.8 / 8.8 EER
- Electronic Control with Electronic Thermostat
- 3 Cooling / 3 Fan Speeds
- Energy Saver Switch for Reduced Energy Consumption
- 24-Hour Timer with Sleep Mode
- Circulaire-Oscillating Louvers for Enhanced Air Circulation
- 2,500 / 2,440 Watts / 11.6 / 12.6 Amps
- 7.0 Dehumidification (pints / hr)
- 510 CFM (High)
- Slide-Out Chassis
- One Touch Lift-Out Filter for Easy Cleaning
- Plug Type—Perpendicular
- EZ Mount Window Installation
- Model ASM22DB