



LOW HEIGHT REMOTE BACK BAR REFRIGERATOR
 2-, 3- and 4-Door (Standard)



BBRLP48 shown

| | |
|-----------|--|
| JOB | |
| AREA | |
| ITEM NO. | |
| MODEL NO. | |

| MODELS | |
|---------|--------------|
| BBRLP48 | 2-Door Model |
| BBRLP72 | 3-Door Model |
| BBRLP96 | 4-Door Model |

NSF/ANSI Standard 7 Listed for open food storage.
 Note: All remote back bars are made to order and non-returnable.

KEY PRODUCT FEATURES AND BENEFITS

- Remote back bar refrigerators allow customers to mount the compressor in an alternate location, ideal for remote servicing and noise isolation
- Stainless steel interior and top standard on all Perlick Back Bar refrigeration for long life durability and easy to clean hygienic storage
- 2" Foamed-in-place insulation provides energy savings using Ecomate(tm), a blowing agent that has zero-ozone depletion and zero global warming potential
- NSF/ANSI Standard 7 Listed for open food, beverage, and garnish storage
- Anti-sweat heaters in cabinet face prevents condensation from forming on door, extending door gasket life and protecting flooring below from damage or slip hazards
- Multiple door styles available in any compartment
 - Choose between Glass, Stainless-Steel, Black Vinyl, or Customer Provided Overlay
 - Drawers not available on remote models

Quick Features:

- Integrated door locks standard on all units
- Optional condensing units available
- Choose between three temperature ranges
 - Refrigerator (34°F-42°F) Factory set to 38°F
 - White Wine (40°F-65°F) Factory set to 45°F
 - Red Wine (40°F-65°F) Factory set to 60°F
- Choose between 6000K white LED lighting or cool blue display lighting
- Choose between flat shelving and wine racks for each compartment
- Choose between Full Length, 6" Chrome, or pull tab style handles
- 1 Year Parts and Labor Warranty



LOW HEIGHT REMOTE BACK BAR REFRIGERATOR
 2-, 3- and 4-Door (Standard)

| MODEL NOS. | | BBRLP48 | BBRLP72 | BBRLP96 |
|---------------------------------------|---------------------------------|--------------------------------|--------------------------------|--------------------------------|
| NUMBER OF DOORS | | 2 | 3 | 4 |
| EXTERIOR CABINET DIMENSIONS | Length - in. (mm) | 48 (1219) | 72 (1829) | 96 (2438) |
| | Depth - in. (mm) | 24¾ (629) | 24¾ (629) | 24¾ (629) |
| | Height - in. (mm) | 29 (736) | 29 (736) | 29 (736) |
| INTERIOR CABINET DIMENSIONS | Length - in. (mm) | 44 (1118) | 68 (1727) | 92 (2337) |
| | Depth - in. (mm) | 18¾ (476) | 18¾ (476) | 18¾ (476) |
| | Height - in. (mm) | 25⅞ (646) | 25⅞ (646) | 25⅞ (646) |
| INTERNAL VOLUME Net. Cu. Ft. (Litres) | | 12.6 (357) | 19.8 (561) | 27.0 (765) |
| PRODUCT CAPACITY | Case Packed - 12 Oz. Bottle/Can | 221/391 | 351/648 | 468/882 |
| | Staggered - 12 Oz. Bottle/Can | 255/490 | 398/723 | 540/993 |
| SHIPPING WEIGHT Lbs. (kg.) | | 250 (113) | 340 (154) | 465 (210) |
| ELECTRICAL SPECIFICATIONS | Electrical Supply | 120 VAC/60 Hz/1 Ph | 120 VAC/60 Hz/1 Ph | 120 VAC/60 Hz/1 Ph |
| | Running Load Amps | 1.6 | 2 | 2.5 |
| | Electrical Connection | Hard wired | Hard wired | Hard wired |
| | Defrost Initiation | Automatic | Automatic | Automatic |
| | Defrost Type | Off cycle | Off cycle | Off cycle |
| | Lighting Type | LED | LED | LED |
| REFRIGERATION SPECIFICATIONS | Evaporator Capacity - Remotes | 1900 Btu/Hr @ 20° F Evaporator | 2300 Btu/Hr @ 20° F Evaporator | 2300 Btu/Hr @ 20° F Evaporator |
| | Remote Refrigerant Options | R134a and R404a | R134a and R404a | R134a and R404a |
| PLUMBING | Evaporator Condensate | Field plumbed | Field plumbed | Field plumbed |

Wine Temperature refrigerators do not carry NSF Rating for open food storage.
 Wine Temperature units are NSF certified for non-potentially hazardous bottled and canned beverage storage.

! WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about Prop 65, go to P65Warnings.ca.gov.

Form No. Z2428
 Rev. 09.08.23



LOW HEIGHT REMOTE BACK BAR REFRIGERATOR
 2-, 3- and 4-Door (Standard)

Note: Open floor drain not provided on models intended for non-packaged food.

