



BIM62ADAPNR



32" x 14.75" x 22.75" (H x W x D)

15" wide ADA height clear gourmet clear icemaker with automatic defrost, internal pump, complete stainless steel exterior, and panel-ready door

Highlights:

- 32" height fits under lower ADA compliant counters
- Approved for use in both commercial and residential settings
- Panel-ready door lets you effortlessly blend the unit into your own cabinetry

Product Features:

15" Wide Clear Icemaker	Built-in undercounter icemaker ideal for installation in kitchens, wet bars, break rooms, and other settings
Custom style	Panel-ready door trim lets you seamlessly integrate this unit into your kitchen or bar
Built-in undercounter design	Front-breathing design lets you make the best use of space by installing your appliance under the counter
Easy panel installation with included 2-piece bracket kit	Enhanced panel execution allows the unit to be flush with cabinets (recommended panel size: 3/4" thickness at 28 1/4" H x 14 5/8" W)
Stainless steel front finish	Fully finished door also allows you to choose a traditional stainless steel front if not installing an overlay panel
Fully articulating door hinge	European style hinge design ensures a flush fit and allows for a smoother opening
Versatile design	Innovative panel-ready bracket kit allows easy custom panel installation, but can also be removed cleanly if you redesign your space and prefer the look of a fully finished stainless steel door
ADA-compliant	32" height allows installation under lower ADA-compliant counters

Height adjustable	Leveling legs can be extended up to 2 1/4", with a slide-out kickplate that allows you to raise the overall height from 32" up to 34 1/4" if used under higher cabinets
-------------------	---

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. ISO 9002:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799 info@summitappliance.com  www.summitappliance.com



BIM62ADAPNR Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Width	14.75" (37 cm)
Depth	22.75" (58 cm)
Depth with Panel	23.5" (60 cm)
Depth with door at 90°	38.13" (97 cm)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	6.0
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101156200
Icemaker	
Door Swing	RHD
Reversible	Yes
Height Adjustable	Yes
Drain Required	Yes
Daily Ice Production	68.0 lbs. (31 kg)
Ice Storage Capacity	26.0 lbs. (12 kg)
Ice Shape	Top hat
Size of Cube	1 1/4" H x 1 1/8" W x 1 1/8" D
Number of Ice Cube Sizes	3
Refrigerant Type	R600a
Refrigerant Amount	1.58 oz.
Interior Height	19.75" (50 cm)
Interior Width	12.25" (31 cm)
Interior Depth	15.5" (39 cm)
Level Legs	4

