

DA 2518

Insert ventilation hood
with energy-efficient LED lighting and backlit controls for easy use.



- Customized kitchen design – fully integrated in 43 1/2 (1102) in (mm) width
- Unique user convenience – Con@ctivity
- Powerful – 500.29 (850) ft³/min (m³/h) in Booster level
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean – Miele CleanCover

EAN: 4002516024699 / Material number: 10876740 /
Old Material Number: 28251855USA

General information	
Model number	DA 2518
Manufacturer material number	10876740
EAN number	4002516024699
Marketing class	Gold
Design	
Insert ventilation hood	•
Construction type and design	
Color	Stainless steel
Operating modes	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
OdorFree charcoal filter (order separately)	DKF 15-P
User convenience	
Miele@home	•
Con@ctivity	•
Electronic controls	•
Operation	Light-touch switches with LEDs
Power levels (number excl. Intensive)	3
Run-on time 5/15 min.	•
Booster levels	1
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	3
Lighting	
Number x W	4 x 3 W
Light intensity in lx	520 lx
Color temperature in K	3000 Kelvin
Blower	
Dual-action blower	•
Exhaust air	
Air throughput in CFM in Booster	500
Air throughput with Booster level 1 (m ³ /h) according to EN 61591	500.29 (850)
Safety	
Safety shut-off	•
Technical data	
Canopy width in in.(mm)	43 1/2 (1102)
Canopy height in in.(mm)	2 (50)
Canopy depth in in.(mm)	15 7/8 (402)
Net weight in lbs. (kg)	32 (14.3)
Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Minimum height above electric cooktops in mm	24 1/8 (610)

DA 2518

Insert ventilation hood

with energy-efficient LED lighting and backlit controls for easy use.



EAN: 4002516024699 / Material number: 10876740 /
Old Material Number: 28251855USA

Minimum safety distance above gas cooktops (max.
12.6 kW total power, burner \leq 4.5 kW) in mm 26 (660)

Plug type	NEMA plug: 5-15
-----------	-----------------

Number of phases	1
------------------	---

Total connected load in kW	0.36
----------------------------	------

Voltage in V	120
--------------	-----

Fuse rating in A	15
------------------	----

Frequency in Hz	60
-----------------	----

Installation note	
--------------------------	--

Vent connection at top	•
------------------------	---

Diameter of vent connection in in.(mm)	6 (150)
--	---------

Standard accessories	
-----------------------------	--

Non-return flap	•
-----------------	---