

DA 6596 D Puristic Canto Island décor hood

with energy-efficient LED lighting and backlit controls for easy use.



- Timeless design – stainless steel canopy 35 3/8 (898) in (mm) wide
- Unique convenience – Con@ctivity 2.0
- Powerful – ?? in Booster level
- Efficient and beautiful – Multi-zone edge extraction
- Variable: edge vented panels made of glass or stainless steel

EAN: 4002515524817 / Material number: 09762240 /
Old Material Number: 28659655USA

General information	
Model number	DA 6596 D Puristic Canto
Manufacturer material number	09762240
EAN number	4002515524817
Marketing class	Gold
Design	
Island ventilation hood	•
Construction type and design	
Color	Stainless steel
Operating modes	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUI 32
OdorFree charcoal filter (order separately)	DKF12-900
Decor elements in glass (order separately)	DRP 6590D
Design	
Multi-zone edge extraction	•
User convenience	
Automatic function	Con@ctivity 2.0
Electronic controls	•
Operation	Light-touch sw.w.LEDs+r. contr.
Power levels (number excl. Intensive)	3
Run-on time 5/15 min.	•
Booster levels	1
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
Acoustic package	•
CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	3
Lighting	
Number x W	4 x 3 W
Light intensity in lx	540 lx
Color temperature in K	3500 Kelvin
Blower	
Dual-action blower	•
Safety	
Safety shut-off	•
Technical data	
Canopy width in in.(mm)	35 3/8 (898)
Overall min. height for vented and external in in. (mm)	27 1/4 (690)
Overall max. height for vented and external in in. (mm)	39 (990)
Canopy height in in.(mm)	2 7/8 (70)
Overall min. height for recirculation in in. (mm)	29 5/8 (750)
Canopy depth in in.(mm)	23 5/8 (598)
Overall max. height for recirculation in in. (mm)	41 3/4 (1060)
Net weight in lbs. (kg)	75 (34.0)

DA 6596 D Puristic Canto

Island décor hood

with energy-efficient LED lighting and backlit controls for easy use.



EAN: 4002515524817 / Material number: 09762240 /
Old Material Number: 28659655USA

Hard-wired	•
Minimum height above electric cooktops in mm	24 1/8 (610)
Minimum safety distance above gas cooktops (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	26 (660)
Plug type	Without plug
Number of phases	1
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Frequency in Hz	60
Installation note	
Vent connection at top	•
Diameter of vent connection in in.(mm)	6 (150)
Telescopic chimney	•
Standard accessories	
Non-return flap	•
Communication module for Con@ctivity XKM 2000 DA	XKS 3000 Z

