

## DAS 8930

Built-in ventilation hood

with intuitive SmartControl White controls for use in narrow upper cabinets



- Intricate design – flat stainless-steel panel, 36 in (90 cm) wide
- Unique user convenience – Con@ctivity
- LED strip for uniform lighting
- Efficient filtration- 10-ply stainless steel grease filters
- Recirculation mode – Active AirClean or Longlife AirClean filter

EAN: 4002516495628 / Material number: 11878590 /  
Old Material Number: 28S8930SUSA

<b>General information</b>	
Model number	DAS 8930
Manufacturer material number	11878590
EAN number	4002516495628
Marketing class	Platinum
<b>Design</b>	
Built-in ventilation hood	•
<b>Construction type and design</b>	
Color	Stainless steel
<b>Operating modes</b>	
Recirculated mode	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
OdorFree charcoal filter (order separately)	DKF 31-P, DKF 31-R
<b>User convenience</b>	
Miele@home	•
Automatic function	Con@ctivity 3.0
Con@ctivity	•
Electronic controls	•
SmartControl	•
Run-on time 5/15 min.	•
Booster levels	2
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
CleanCover	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
<b>Lighting</b>	
Number x W	1 x 3 W
Light intensity in lx	270 lx
Color temperature in K	3500 Kelvin
Light dimmer function	•
<b>Blower</b>	
Dual-action blower	•
<b>Exhaust air</b>	
Air throughput in CFM in Booster	495
Air throughput with Booster level 1 (m <sup>3</sup> /h) according to EN 61591	494.41 (840)
<b>Safety</b>	
Safety shut-off	•
<b>Technical data</b>	
Canopy width in in.(mm)	34 (861)
Canopy height in in.(mm)	2 3/8 (60)
Canopy depth in in.(mm)	12 1/8 (307)
Net weight in lbs. (kg)	42 (19.0)
Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Minimum height above electric cooktops in mm	24 1/8 (610)

DAS 8930

Built-in ventilation hood

with intuitive SmartControl White controls for use in narrow upper cabinets



EAN: 4002516495628 / Material number: 11878590 /  
Old Material Number: 28S8930SUSA

Minimum safety distance above gas cooktops (max.  
12.6 kW total power, burner  $\leq$  4.5 kW) in mm 26 (660)

Plug type NEMA plug: 5-15

Number of phases 1

Total connected load in kW 0.35

Voltage in V 120

Fuse rating in A 15

Frequency in Hz 60

#### Installation note

Vent connection at top •

Vent connection at top and rear •

Installation template •



#### Standard accessories

Non-return flap •

## DAS 8930



Built-in ventilation hood

with intuitive SmartControl White controls for use in narrow upper cabinets



DAS8930, Installation drawings

1) Extraction, recirculation with conversion kit DUU 150.,  
 2) Alternative ducting connection to the rear., 3)  
 Accessory DSM module., 4) The wall unit can be fitted  
 with a partition after installation. The slots for the grease  
 filters and, in recirculation mode, for the odor filters  
 must remain accessible., The height of the wall unit  
 and the cut-out dimensions must take into account  
 any accessories fitted (e.g. silencer, recirculation hood  
 conversion kit, DSM module)



DAS8930, drawing – US

1) Exhaust air, recirculation with DUU 150 conversion  
 kit., 2) Exhaust air connection alternatively to the rear., 3)  
 DSM module accessory., 4) The wall unit can be fitted  
 with a partition after installation. The slots for the grease  
 filters and, in the case of recirculation mode, for the odor  
 filters must remain accessible. , Mounted accessories  
 must be taken into account for the cabinet height and cut-  
 out dimensions (e.g. silencer, recirculation air conversion  
 kit, DSM module).