



Electrolux |

ICON

# Over-the-Range Microwave

professional series

E30MH65QPS



## PRODUCT DIMENSIONS

|        |          |
|--------|----------|
| Height | 17-9/16" |
| Width  | 29-7/8"  |
| Depth  | 17-1/16" |

## MORE EASY-TO-USE FEATURES

### Second-Tier Rack

Creates more space in your microwave, allowing you to heat more food at once.

### Automatic Settings

## Signature Features



### Automatic Cooking Options

Pre-programmed settings give you the versatility to combine both microwave cooking and convection heat.



### One-Touch Options

One-touch options include Reheat, Add 30-Seconds, Popcorn and Defrost.



### Convection Cooking

Circulates hot air through your microwave to cook foods evenly.



### Five-Speed Ventilation

Control the fan speed with the touch of a button to adjust the airflow based on your cooking needs.

# Over-the-Range Microwave

E30MH65QPS professional series



## 30" OVER-THE-RANGE MICROWAVE

|                                |                 |
|--------------------------------|-----------------|
| Oven Cavity                    | 1.8 Cu. Ft.     |
| Watts                          | 1,050           |
| Oven Interior                  | Stainless Steel |
| Interior Light                 | Yes             |
| Cooktop Light w/ Touch Control | Yes             |
| Glass Turntable Diameter       | 14-3/16"        |

## PANEL FEATURES

|                                        |               |
|----------------------------------------|---------------|
| Electronic Clock & Timer               | Yes           |
| 2-Line Scroll Cooking Display          | Yes           |
| Lock                                   | Yes           |
| Demo Mode                              | Yes           |
| Start/Enter                            | Yes           |
| Stop/Clear                             | Yes           |
| Stoppable Turntable                    | Yes           |
| On/Off Sound Control                   | Yes           |
| User Selectable Signal                 | Yes           |
| Daylight Savings Time                  |               |
| Power Levels                           | 10            |
| Touch Pad Controls                     | 34            |
| Convenience Options –                  |               |
| Sensor Cook Categories                 | 5             |
| Popcorn Button                         | Yes           |
| Sensor Reheat Categories               | 4             |
| Snack Categories                       | 4             |
| Auto Cook Categories                   | 5             |
| Auto Defrost Categories                | 3             |
| Melt/Soften/Warm Options               |               |
| Add 30 Seconds                         | Yes           |
| Convection Cook (Variable Temperature) | 100° – 450° F |
| Microwave Convection Categories        | 4             |
| Combination Cook                       |               |
| Stage Cooking (Cook I & II)            |               |

## VENTILATION SYSTEM

|                                                             |              |
|-------------------------------------------------------------|--------------|
| Exhaust Duct                                                | Convertible* |
| 4-Speed Exhaust Fan (400 CFM)                               | Yes          |
| On/Off                                                      | Yes          |
| Delay Off                                                   |              |
| Auto On - High Speed (2 Level)                              | Yes          |
| Charcoal Filters (Recirculated Installation)/Grease Filters | 1/2          |

## POWER RATINGS

|                                         |               |
|-----------------------------------------|---------------|
| Microwave – (Watts @ 120 Volts)         | 1050          |
| Convection – (Watts @ 120 Volts)        | 1500          |
| Amps @ 120 Volts                        | 15            |
| Frequency (MHz)                         | 2450          |
| Voltage Rating                          | 120V/60Hz/20A |
| Connected Load (kW Rating) @ 120 Volts† | 1.65          |

## ACCESSORIES

|                                      |          |
|--------------------------------------|----------|
| Two-Position Adjustable Rack         | Included |
| 36" Filler Panel Kit – PN# MWFILKTSS | Optional |

## SPECIFICATIONS


|                           |                |
|---------------------------|----------------|
| Power Cord Location       | Right Top Rear |
| Shipping Weight (Approx.) | 84 Lbs.        |

\*Ventilation is convertible to be either ducted outside, or recirculated inside requiring no ducting.

†For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.

NOTE: Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at [electroluxicon.com](http://electroluxicon.com).

Specifications subject to change.



## PRODUCT DIMENSIONS

|                                         |          |
|-----------------------------------------|----------|
| Height (Including 1/2" Lower Extrusion) | 17-9/16" |
| Width                                   | 29-7/8"  |
| Depth                                   | 17-1/16" |

## OVEN CAVITY DIMENSIONS

|        |           |
|--------|-----------|
| Height | 9-15/16"  |
| Width  | 21-1/4"   |
| Depth  | 14-23/32" |

## Electrolux Major Appliances, N.A.

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-877-4electrolux (1-877-435-3287) • [electroluxicon.com](http://electroluxicon.com)  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • [electroluxicon.ca](http://electroluxicon.ca)

E30MH65QP 11/15


© 2015 Electrolux Home Products, Inc.



High standards of quality at Electrolux Home Products, Inc. mean we are constantly working to improve our products. We reserve the right to change specifications or discontinue models without notice.


Locate 120V/60Hz grounded outlet inside upper cabinet

Microwave MUST be mounted to BOTH a top cabinet AND a wall\*



\*Can NOT be installed in island or peninsula cabinet arrangements

†If cabinet depth including cabinet doors is greater than 13", then unit needs spaced out from wall using adequate materials capable of supporting a total load of 150 lbs., to allow for proper top vent air exhaust



## 30" Over-the-Range Microwave Specifications

- Product Weight – 69 Lbs.
- Voltage Rating – 120V/60Hz/20 Amp
- Connected Load (kW Rating) @ 120 Volts = 1.65kW  
(For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 120 Volts = 15 Amps
- Always consult local and national electric codes.
- Grounded outlet should be located in cabinet above, with hole in base to route power cord. Carefully follow top template instructions for power cord clearance when installing beneath smooth, flat cabinets.
- Microwave's ventilation system is preset to recirculate air inside with no ducting system required. Exhausting air outside is optional, using either vertical or horizontal ducting system. (Refer to Ducted Option Specifications for outside ventilation.)
- For safe and proper installation, microwave MUST be mounted to BOTH a top cabinet AND a wall, and connected to at least one wall stud. Can NOT be installed in island or peninsula cabinet arrangements.
- Cabinet bottom MUST be level to insure proper installation.
- Cabinet MUST be capable of supporting a total load of 150 lbs.
- Filler blocks recommended for installation when cabinet front hangs below recessed bottom shelf.
- Minimum distance of 30" required from cooking surface to bottom edge of top cabinet.
- Minimum distance of 66" required from floor to top of microwave.
- Opening between cabinets MUST be 30" wide and free of obstructions.
- Allow 25-1/2" minimum clearance for 90° door swing.

## Ducted Option Specifications

- For outside ventilation.
- Exhaust duct adapter supplied assembled for outside ventilation, designed to mate with standard 3-1/4" x 10" rectangular duct. If round duct required, rectangular-to-round transition adapter will be needed with 5"/6" diameter.
- For most efficient airflow exhaust, use a straight run or as few elbows as possible with maximum duct length of 3-1/4" x 10" rectangular or 5"/6" diameter round duct, not to exceed 120 equivalent feet.
- For horizontal installation, be sure to allow enough space between wall studs to accommodate exhaust.
- Refer to installation instructions on web for detailed duct preparation and converting exhaust vent blower system for exterior exhaust ventilation.

**Note:** For planning purposes only. Refer to Product Installation Guide on the web at [electroluxicon.com](http://electroluxicon.com) for detailed instructions.

## Optional Accessories

- 36" Filler Panel Kit – (PN # MWFILKTSS).

## Electrolux Major Appliances, N.A.

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-877-4electrolux (1-877-435-3287) • [electroluxicon.com](http://electroluxicon.com)  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • [electroluxicon.ca](http://electroluxicon.ca)