

Dual-Fuel Freestanding Range

E36DF76GPS professional series



Smooth-Glide® Oven Racks

Ball bearing oven racks glide with unparalleled ease and extend fully for effortless access.



Min-2-Max Burners®

With the widest range of BTU performance in the industry, these best-in-class dual-flame sealed burners offer unrivaled versatility—from a roaring 18,000-BTU boil to a gentle 450-BTU simmer.



CustomConvect^{3™} Convection Technology

Distributes heat evenly throughout the oven by adding a third cooking element plus a variable speed fan.



Extra-Large Oven Capacity

Spacious 6.4 cubic foot interior gives you all the cooking space you need.

36" DUAL-FUEL FREESTANDING RANGE

CONTROL PANEL FEATURES

Electronic Oven Control	Yes
Professional-Style Stainless Steel Console	Yes
Large Professional Skirted Knobs with Bezel	8

RANGETOP FEATURES

Min-2-Max Burners® (BTU)	2 (18,000 – 450)
Sealed Power Burner™ (BTU)	2 (14,000)
Sealed Precision Burner™ (BTU)	1 (9,500) 1 (5,000)
Continuous Grates	3
Electronic Ignition	Yes

OVEN CAVITY FEATURES

Capacity	6.4 Cu. Ft.
Bake Element (Watts)	3000
Broil Element (Watts)	4000
Convection Element (Watts)	2500
Signature Cobalt Blue Oven Interior	Yes
CustomConvect ^{3™} Convection System	Yes
Self-Clean with Door Lock	Yes
Extra-Wide Oven Window	Yes
Halogen Oven Light	2
Eight-Pass Bake & Broil	Yes
Smooth-Glide® Oven Racks	3
Conventional Rack	1
Convection Roasting Rack	1
Hidden Bake Element	Yes

ADDITIONAL FEATURES

Stainless Steel Backsplash	6"
Full Stainless Steel Side Panels	Yes
Professional Handle	Yes
Fully Adjustable, Heavy-Duty Legs	Yes

ACCESSORIES

Broil Pan and Insert	Included
Stainless Steel Cleaner	Included
Griddle	Included
Wok Ring	Included
Simmer Plate	Included
9" Stainless Steel Backsplash – PN# 903104-9100	Optional
12" Stainless Steel Backsplash – PN# 903105-9100	Optional
4" Stainless Steel Kick Plate – PN# 318352652	Optional
Stainless Steel Island Trim Kit – PN# 903106-9100	Optional
Black Knobs Kit – PN# 903108-9020	Optional

SPECIFICATIONS

Oven Cavity Dimensions –	
Height	18-3/4"
Width	30-1/8"
Depth	19-5/8"
Product Dimensions –	
Height (Including Adjustable Legs)	41-5/8 – 42-5/8"
Width	35-7/8"
Depth (Including Handle) (with 90° Door Open)	28-3/4" 47-3/8"
Gas Supply Connection Location	Left Bottom Rear
Power Supply Connection Location	Right Bottom Rear
Amps @ 240/208 Volts	27/23
Minimum Circuit Required (Amps)	30
Connected Load (kW Rating) @ 240/208 Volts	6.5/4.8
LP Gas Conversion Kit	Included
Shipping Weight (Approx.)	404 Lbs.

NOTE: Always consult local and national electric and gas codes. Refer to Product Installation Guide for detailed installation instructions on the web at electroluxicon.ca.

Specifications subject to change.

