



<i>EAN code</i>	<i>8034122370293</i>
<i>Model Code</i>	<i>FIVAL28B6SS-R Built-in - 28" (72 cm) - inox - 600 CFM</i>
<i>Collection</i>	<i>Built-in</i>

FEATURES AND PROPERTIES

<i>Materials/Finishes</i>	<i>Scotch brite stainless steel (AISI 304)</i>
<i>Lighting</i>	<i>Strip LED Dynamic Light (2700K - 5600K)</i>
<i>Control</i>	<i>Electronic control</i>
<i>Installation type</i>	<i>Insert</i>
<i>Ducting type</i>	<i>External ducting/Recirculating</i>
<i>Filters</i>	<i>Metallic grease filter, removable and washable Charcoal filter (optional)</i>
<i>*Chimney</i>	<i>Possible to duct wall mounted from rear</i>
<i>Dimensions</i>	<i>28 in</i>
<i>Features</i>	<i>Perimeter suction Possible to duct wall mounted from rear SRS Speed reduction system</i>

OPTIONAL ACCESSORIES

<i>Code</i>	<i>Description</i>
103050091	FFCHAR3COBL - Round charcoal filter Ø 6" - Type 6
105080053	Remote control
KACL.815	Protective cleaning cloths for stainless steel (box 10 pcs)

ELECTRICAL CONNECTION AND CONSUMPTION

<i>Maximum consumption</i>	<i>340W</i>
<i>Voltage/Frequency</i>	<i>110-120V 60Hz</i>
<i>Connection type</i>	<i>Hood comes standard with Nema 5-15P power cord</i>

BLOWER PERFORMANCE

<i>Motor</i>	<i>600 CFM</i>
--------------	----------------

TECNICAL SPECS OF COOKERHOOD WITH 600 CFM MOTOR

Motor Speed	1	SRS 2* 2	SRS 3* 3	4
CFM (rated at the motor)	210	295	395	600
Sones (estimated value)	1.5	3	4.25	6
Duct Size	6"	6"	6"	6"

*If activated SRS has 2 settings; 3 speed max & 2 speed max

WEIGHTS AND DIMENSIONS

<i>Gross weight</i>	<i>31 lbs</i>
<i>Net weight</i>	<i>24 lbs</i>
<i>Packaging dimensions</i>	<i>L 32 in H 16 in D 16 in</i>