

Single Wall Oven, 30", Stainless Steel HBL5751UCC



The Bosch Speed Microwave Combination Oven Features Heavy Metal Stainless Steel Knobs.

- **Top-/Bottom heat:** perfect results on one level thanks to optimal distribution of heat.
- **Self-Clean Mode:** cleans the oven with a 2,3, or 4 hour self-clean cycle
- **Convection Multi-Rack:** uses a third heating element and fan to evenly circulates air around the cavity so you get consistently even results.
- **TFT Display:** easily switch between oven modes on this easy to see control panel -- featuring SteelTouch™ Buttons.
- **Ideal for preparing of frozen pizza.**

UPC code: 825225908869
 Product color: Stainless Steel
 Energy source: Electric
 Watts: 5000 W
 Fuse protection:30 A
 Volts: 240/208 V
 Frequency: 60 Hz
 Power Cord Length: 50"
 Plug Type: No Plug, Fixed Connection
 Required Cutout Size (HxWxD) (in): 27" - 28 5/8" x 28 1/2" x 23 1/2"
 Product Packaging Dimensions (HxWxD): 33.99 x 33.99 x 30.99
 Net Weight: 176.000 lbs
 Gross Weight: 193.000 lbs



HEZTR301 Telescopic Oven Rack 30"

Single Wall Oven, 30", Stainless Steel HBL5751UCC

The Bosch Speed Microwave Combination Oven Features Heavy Metal Stainless Steel Knobs.

- Speed Microwave Oven: For Additional Details Please Review SKU HMC80251UC

Design

- Industrial-style design heavy-duty metal knobs have a premium look and feel

Performance

- 11 Specialized Cooking Modes - Gourmet Cooking Made Easy
- Custom Cooking Modes: Pizza, Pie, Warm and Proof
- Genuine European Convection for Even Baking Results on Multiple Racks.
- Temperature Conversion for Convection Cooking

Efficiency

- EcoClean™ 2-Hour Self-Clean Cycle

Convenience


- One Oven Light to Better Monitor Cooking Progress
- Extra Large Door Window for Easy Monitoring of Cooking Process
- Star-K Certified. Temperature Range: 100° - 450° F

Capacity

- Large Capacity at 4.6 Cu Ft.
- Recessed 8 Pass Broil Element for Increased Capacity and Safety

Single Wall Oven, 30", Stainless Steel

HBL5751UCC



* Junction box may be installed above, below, or to the left or right of the unit within range of the power conduit.

measurements in inches (mm)

