





GE Appliances

JKP15AAAA - GE 27" Single Wall Oven

Dimensions (in inches)



KW Rating	
240V	3.4
208V	2.6
Breaker Size	
20 Amps [†]	

[†]**Note:** Check local codes for required breaker size

Installation Information: Before installing, consult installation instructions [Pub. No. 31-10200] packed with product for current dimensional data.

Note: Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°

For answers to your Monogram®,
GE Profile Performance Series™,
GE Profile™ or GE appliance questions, call
GE Answer Center® service, 800.626.2000.



Listed by
Underwriters
Laboratories




GE Appliances

JKP15AAAA - GE 27" Single Wall Oven

Dimensions (in inches)

Locate thermal oven junction box either 5" MIN. below cutout floor or approximately 54" MIN. above cutout floor.

For Microwave:
Locate 120V, 60 cycle grounded power receptacle within shaded area.



Note: Recommend approximately 1/4" gap between microwave trim and wall oven trim. (The 2-1/4" dimension should create a 1/4" gap.) Allow 1-1/2" for overlap of the Microwave Oven Kit Trim over all edges of the trim kit cutout.

Installation Information: Before installing, consult installation instructions packed with accessory trim kit, microwave oven and single oven for current dimensional data.

Microwave oven should be installed on a 3/8" plywood base and supported by 2"x4" or 1"x4" equivalent runners on all sides. Base must be capable of supporting a minimum of 100 lbs.

Note A:
21" MIN. receptacle in cabinet.
19" MIN. receptacle outside cabinet.

For answers to your Monogram®, GE Profile Performance Series™, GE Profile™ or GE appliance questions, call GE Answer Center® service, 800.626.2000.




GE Appliances

JKP15AAAA - GE 27" Single Wall Oven

Dimensions (in inches)

Gas or electric cooktops may be installed over this oven.
See cooktop installation instructions for cutout size.
See label on top of oven for approved cooktop models

Gas and electrical connections for gas cooktop must be located in an adjacent accessible location to the right



*32" MIN. from top of countertop (1-1/2) to top of runners must be

Note: Oven is rated for use only under 30" gas (standard or sealed burner) and 30" electric (CleanDesign and Calrod®) cooktops. Excludes Induction Cooktops.

Installation Information: Before installing, consult installation instructions (Pub. No. 31-10200) packed with product for current dimensional data.

Specification Revised 6/99

For answers to your Monogram®,
GE Profile Performance Series™,
GE Profile™ or GE appliance questions, call
GE Answer Center® service, 800.626.2000.




Listed by
Underwriters
Laboratories




GE Appliances

JKP15AAAA - GE 27" Single Wall Oven

Sealed Burner Gas Cooktop Installation Dimensions (in inches)



Standard Burner Gas Cooktop Installation Dimensions (in inches)



Specification Revised 6/99

Note: Oven is rated for use only under 30" gas (standard or sealed burner) and 30" electric (CleanDesign and Calrod®) cooktops. Excludes Induction Cooktops.

Installation Information: Before installing, consult installation instructions packed with wall oven and cooktop, or installation instructions [Pub. No. 31-10200] packed with product for current dimensional data.


For answers to your Monogram®,
GE Profile Performance Series,™
GE Profile™ or GE appliance questions, call
GE Answer Center® service, 800.626.2000.





GE Appliances

JKP15AAAA - GE 27" Single Wall Oven



Features and Benefits

- TrueTemp™ System
- Large Capacity Self-Clean Oven with Automatic Oven Door Lock
- 2 Oven Racks / 4 Embossed Rack Positions
- SmartSet Electronic Oven Controls
- Electronic Clock and Kitchen Timer
- Delay Time Bake Option with Cook and Hold
- Auto Oven Shut-Off with Override
- Variable Broil
- Broiler Pan with Grid
- Interior Oven Light
- Frameless Glass Oven Door with Big View Window
- Sure Grip Designer-Style Handle
- 27" Oven Cabinet Width Required
- Undercounter Installation Option
- Model JKP15WAWW - White on white
- Model JKP15BABB - Black on black
- Model JKP15AAAA - Almond on almond