





Profile™

JTP56BABB - GE Profile™ 30" Double Wall Oven

Dimensions (in inches)



MOST 30" WALL CABINETS CAN BE USED WITH THIS UNIT
THE OPENING BETWEEN THE INSIDE WALLS MUST BE AT LEAST 28-1/2" WIDE



KW Rating	
240V	7.2
208V	5.4
Breaker Size	
240V	40 Amps [†]
208V	30 Amps [†]

Cabinet	30"
A – Overlap of Oven Over Side Edges of Cutout	11/16" – 3/4"
B – Overlap of Oven at Bottom of Cutout	1"
Oven	
C – Overall Depth	23-1/2"
D – Overall Height	52-15/16"
E – Overall Width	30"

[†]Note: Check local codes for required breaker size

Installation Information: Before installing, consult installation instructions [Pub. No. 31-10198] packed with product for current dimensional data.

Note: Cabinets installed adjacent to wall ovens must have an adhesion spec of at least 194°


For answers to your Monogram®, GE Profile Performance Series™, GE Profile™ or GE appliance questions, call GE Answer Center® service, 800.626.2000.



Listed by
Underwriters
Laboratories



JTP56BABB - GE Profile™ 30" Double Wall Oven



Features and Benefits

- TrueTemp™ System
- Convection Upper Oven:
 - Extra Large Capacity Self-Clean Oven with Delay Clean Option
 - 3 Oven Racks / 7 Embossed Rack Positions
 - Convection Bake
 - Convection Roast
 - Roasting Rack
- Thermal Lower Oven:
 - Extra Large Capacity Self-Clean Oven with Delay Clean Option
 - 2 Oven Racks / 6 Embossed Rack Positions
- SmartSet Electronic Oven Controls with Digipad
- Broiler Pan with Grid
- Up-Front Oven Lights
- Big-View Windows
- Hidden Bake Elements
- Variable Broil / Six-Pass Broil Element
- Automatic Meat Thermometer
- Integrated Designer-Style Handles
- 30" Oven Cabinet Width Required
- JTP56WAWW - White on white
- JTP56BABB - Black on black
- JTP56AAAA - Almond on almond