



# SBC682PNRCMTWIN



33.63" x 23.75" x 24.75" (H x W x D)

24" wide indoor/outdoor dual tap combination cold brew/nitro coffee dispenser for built-in or freestanding commercial or residential use, with panel-ready door, stainless steel exterior, and caster set

### Highlights:

Customizable door accepts full overlay panels for a seamless look that can blend into cabinetry

Commercially approved to NSF-7 standards

Unique tap combination allows you to serve both nitro and regular cold brew on tap from two separate sixtel kegs

### Product Features:

|                                      |                                                                                                                                                                                                           |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Full-sized coffee dispenser          | 5.6 cu.ft. interior can accept a full half barrel or quarter keg, or up to three sixth barrels or Cornelius style kegs                                                                                    |
| Dispenses both flat and nitro coffee | Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts                                                                                            |
| Panel-ready door                     | Extended hinging allows you to install your own panel overlay on the door, creating a custom look to complement or blend into your own cabinetry (panel size: 29 3/4" H x 23 5/16" W at a 3/4" thickness) |
| Commercially approved                | ETL-S listed to NSF-7 standards and meets UL-471 for use in commercial settings                                                                                                                           |
| Weatherproof design                  | Solid 304 grade stainless steel construction allows placement in the outdoors                                                                                                                             |
| Built-in capable                     | Front-breathing design allows fully recessed installation under counters                                                                                                                                  |
| Complete dual tap kit                | Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs                                 |
| Dual tap system                      | Twin draft tower allows you to serve from two 1/6 (sixel) sized kegs                                                                                                                                      |
| Automatic defrost                    | Reduced user maintenance with auto defrost operation                                                                                                                                                      |



SBC682PNRCMTWIN Specifications:

| Overview                   |                              |
|----------------------------|------------------------------|
| Nominal Width              | 24.0" (61 cm)                |
| Nominal Depth              | 25.0" (64 cm)                |
| Nominal Height             | 34.0" (86 cm)                |
| Height of Cabinet          | 33.63" (85 cm)               |
| Width                      | 23.75" (60 cm)               |
| Depth                      | 24.75" (63 cm)               |
| Depth with door at 90°     | 46.75" (119 cm)              |
| Capacity                   | 5.6 cu.ft. (159 L)           |
| Defrost Type               | Automatic                    |
| Door                       | Panel-Ready                  |
| Cabinet                    | Stainless Steel              |
| US Electrical Safety       | ETL                          |
| Canadian Electrical Safety | ETL-C                        |
| Sanitation                 | ETL-S                        |
| Energy Usage/Year          | 305.0kWh/year                |
| Amps                       | 1.25                         |
| Voltage/Frequency          | 115 V AC/60 Hz               |
| Weight                     | 120.0 lbs. (54 kg)           |
| Parts & Labor Warranty     | 1 Year                       |
| Compressor Warranty        | 5 Years                      |
| UPC                        | 761101087474                 |
| Kegeerator                 |                              |
| Door Swing                 | RHD                          |
| Reversible                 | Reversible w/ Optional Hinge |
| Tap Kit                    | Yes                          |
| Height with Tap            | 51.5" (131 cm)               |
| Number of Taps             | 2                            |
| Adjustable Shelves         | Yes                          |
| Shelf Type                 | Chrome                       |
| Shelf Qty                  | 2                            |
| Thermostat Type            | Digital                      |
| Fan Type                   | Interior and Exterior        |
| Refrigerant                | R600a                        |
| Refrigerant Amount         | 1.06 oz.                     |
| High Side PSI              | 150.0                        |

|                   |                            |
|-------------------|----------------------------|
| Low Side PSI      | 50.0                       |
| Inter Height      | 26.75" (68 cm)             |
| Interior Width    | 20.0" (51 cm)              |
| Interior Depth    | 19.0" (48 cm)              |
| Level Legs Qty    | 4                          |
| Wheel Qty         | 4                          |
| Temperature Range | 34°F to 68°F (1°C to 20°C) |
| Sound Level       | 34.0 db                    |

