



TRUE FOOD SERVICE EQUIPMENT, INC. • 2001 East Terra Lane • O'Fallon, Missouri 63366-4434  
ph. 636.240.2400 • toll free 800.325.6152 • fax 636.272.2408 • parts fax 636.272.9471 • www.truemfg.com

|              |          |         |       |
|--------------|----------|---------|-------|
| PROJECT NAME | LOCATION |         | AIA # |
| ITEM #       | QTY      | MODEL # | SIS # |

# SPEC SERIES®

ROLL-THRU GLASS FRONT/SOLID REAR SWING DOOR REFRIGERATOR

|        |               |               |               |
|--------|---------------|---------------|---------------|
| models | STR2RRT-2G-2S | STA2RRT-2G-2S | STG2RRT-2G-2S |
|--------|---------------|---------------|---------------|



## STR2RRT-2G-2S

|          |                                                                 |
|----------|-----------------------------------------------------------------|
| Exterior | Stainless steel door, front & sides.                            |
| Interior | Stainless steel side walls, back, floor, door liner, & ceiling. |


## STA2RRT-2G-2S

|          |                                                                 |
|----------|-----------------------------------------------------------------|
| Exterior | Stainless steel door, front & sides.                            |
| Interior | Aluminum side walls & back.<br>Stainless steel floor & ceiling. |


## STG2RRT-2G-2S

|          |                                                                 |
|----------|-----------------------------------------------------------------|
| Exterior | Stainless steel door, with matching aluminum sides.             |
| Interior | Aluminum side walls & back.<br>Stainless steel floor & ceiling. |


## plan view



ELEVATION



RIGHT VIEW



PLAN VIEW

## SPECIFICATIONS

| Dimensions  | in.      | mm.           |
|-------------|----------|---------------|
| Length      | 68       | 1728          |
| Depth       | 37 1/2   | 953           |
| Height      | 83 3/4   | 2128          |
| Electrical  | U.S.     | International |
| Horsepower  | 1/2      | N/A           |
| Amps        | 9.5      | N/A           |
| Voltage     | 115/60/1 |               |
| NEMA        | 5-15P    |               |
| Cord Length | 9 ft.    | 2.74 M.       |



115/60/1  
NEMA-5-15R

\* Depth does not include 4 1/4" (108 mm) each side for ramps.  
\* Height does not include 1" (26 mm) for system mechanical components.

Specifications subject to change without notice.  
Chart dimensions are rounded up to the nearest 1/8" (millimeters rounded up to the next whole number).



APPROVALS

AVAILABLE AT



|              |          |         |
|--------------|----------|---------|
| PROJECT NAME | LOCATION | AIA #   |
| ITEM #       | QTY      | MODEL # |
|              |          | SIS #   |

# SPEC SERIES®

ROLL-THRU GLASS FRONT/SOLID REAR SWING DOOR REFRIGERATOR

models STR2RRT-2G-2S STA2RRT-2G-2S STG2RRT-2G-2S



## standard features

### REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) 134A refrigerant.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Sealed, cast iron, self-lubricating evaporator fan motor(s) and larger fan blades give True roll-in's a more efficient low velocity, high volume airflow design. This unique design ensures faster temperature recovery and shorter run times in the busiest of foodservice environments.
- Top mounted refrigeration system with evaporator positioned out of food zone to maximize capacity.

### CABINET CONSTRUCTION

- Insulation - Entire cabinet structure and solid door are foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Four (4) heavy gauge stainless steel ramps (one per door).
- Designed to accept roll-in racks (inboard castors) with maximum dimensions of 27"L x 29"D x 66"H (686 mm x 737 mm x 1677 mm)(supplied by others).
- One (1) heavy gauge stainless steel ramp.

### DOORS

- "Low-E", double pane thermal insulated glass.
- Lifetime guaranteed bolt style door locks standard.
- Lifetime guaranteed heavy duty all metal working door handle.
- Positive seal self-closing door with 120° stay open feature. Lifetime guaranteed external cam lift door hinges, Three (3) per door section.

- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.

### LIGHTING

- Incandescent interior lighting, safety shielded.

### MODEL FEATURES

- Exterior digital temperature display, available with either °F or °C .
- Evaporator epoxy coated to eliminate the potential of corrosion
- Interior bumpers protect cabinet walls from abuse caused by roll-in carts.
- NSF/ANSI Standard 7 compliant for open food product.

### ELECTRICAL

- Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.

METRIC DIMENSIONS ROUNDED UP TO THE  
NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE  
WITHOUT NOTICE



| Model           | Elevation | Right | Plan | 3D | Back |
|-----------------|-----------|-------|------|----|------|
| ST( )2RRT-2G-2S |           |       |      |    |      |