

# VT65



33.5" x 23.63" x 23.5" (H x W x D)

Built-in undercounter laboratory freezer capable of -30° C (-22° F) operation

### Highlights:

Commercially listed to NSF-7 standards

Precise temperature control with a digital thermostat

Factory installed lock provides security you can count on

### Product Features:

Built-in capable	Front-breathing system allows the unit to be used built-in
Commercially approved	Meets NSF-7 commercial standards
Slim counter height dimensions	24" footprint fits easily in space-challenged facilities
-30° C (-22° F) capable	Low temperature operation ideal for vaccines, pharmaceuticals, and long-term preservation of frozen food
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened
Factory installed lock	Keyed lock offers convenient security
Digital thermostat	Electronic controls for precise temperature management
Alarm with temperature display	Provides external temperature readout and includes programmable alarm to warn of temperature variations
Manual defrost	No temperature fluctuations with an energy efficient manual defrost system

## VT65 Specifications:

Overview	
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.5" (85 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101009223
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.76 oz.
Interior Drawers	Yes
Drawers Qty	3
Temperature Range	-20°C to -30°C

