

# VT65MLVAC456ADA



32.38" x 23.63" x 23.5" (H x W x D)

Built-in undercounter ADA height -30°C all-freezer certified to NSF/ANSI 456 for vaccine storage, with NIST calibrated thermometer/alarm

**Highlights:**

- Certified to NSF 456 for the storage of vaccines
- Low temperature operation ideal for preserving certain pharmaceuticals
- User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

**Product Features:**

|                                                                                                                                                       |                                                                                                                                                                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certified to NSF/ANSI 456 Vaccine Standard Designed and tested to comply with the new NSF vaccine storage standards through an independent laboratory |                                                                                                                                                                             |
| Reliable temperature stability                                                                                                                        | Engineered to store vaccines and other select pharmaceuticals under stable temperature conditions                                                                           |
| Slim undercounter dimensions                                                                                                                          | 24" footprint is ideal for use under the counter                                                                                                                            |
| ADA Compliant height                                                                                                                                  | Sized at 32" high (32.38" to hinge cap) to fit under lower counters complying with ADA guidelines                                                                           |
| Built-in capable                                                                                                                                      | Front-breathing design allows built-in installation under counters                                                                                                          |
| Low temperature operation                                                                                                                             | Preset and locked at -30°C to prevent accidental adjustments. Range can be adjusted between -15° and -35°C by contacting our technical support team                         |
| Microprocessor control panel                                                                                                                          | Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience                                 |
| High/low temperature alarm                                                                                                                            | Audible alarm sounds if the interior temperature rises or falls out of set range                                                                                            |
| NIST calibrated temperature display                                                                                                                   | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button |

## VT65MLVAC456ADA Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Nominal Height             | 32.0" (81 cm)      |
| Height of Cabinet          | 32.0" (81 cm)      |
| Height to Hinge Cap        | 32.38" (82 cm)     |
| Nominal Width              | 24.0" (61 cm)      |
| Width                      | 23.63" (60 cm)     |
| Nominal Depth              | 24.0" (61 cm)      |
| Depth                      | 23.5" (60 cm)      |
| Depth with Handle          | 25.5" (65 cm)      |
| Depth with door at 90°     | 46.0" (117 cm)     |
| Capacity                   | 1.85 cu.ft. (52 L) |
| Defrost Type               | Manual             |
| Door                       | White              |
| Cabinet                    | White              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S to NSF 456   |
| Amps                       | 1.3                |
| Weight                     | 105.0 lbs. (48 kg) |
| Parts & Labor Warranty     | 2 Years            |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101086903       |
| Freezer                    |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Interior Height            | 24.25" (62 cm)     |
| Interior Width             | 17.63" (45 cm)     |
| Interior Depth             | 17.0" (43 cm)      |
| Thermostat Type            | Digital            |
| Fan Type                   | Exterior           |
| Refrigerant Type           | R134a              |
| Refrigerant Amount         | 2.8 oz.            |
| High Side PSI              | 235.0              |
| Low Side PSI               | 70.0               |
| Level Legs                 | 4                  |
| Interior Drawers           | Yes                |
| Drawers Qty                | 3                  |
| Compressor Step Height     | 5.5" (14 cm)       |

|                       |                |
|-----------------------|----------------|
| Compressor Step Width | 17.63" (45 cm) |
| Compressor Step Depth | 5.5" (14 cm)   |
| Temperature Range     | -15°C to -35°C |

